



Pneumatics products

Logic elements,
Position / Detectors
Electro-pneumatic valves




■ Switching



■ Control systems



■ Directional control



www.crouzet.com



- For over 50 years, Crouzet has established a reputation for providing micro-control products, micro-motors and position sensors. Read on to discover Crouzet's complete offer of Pneumatic products for industrial and explosive atmospheres.
- Always one step ahead of market trends and customer requirements, Crouzet is continually developing its range of both standard and customised automation components and solutions to cover all the latest commercial and industrial applications and meet the needs expressed by manufacturers of automated equipment and machinery.
- Throughout the world, Crouzet the adaptation specialist provides you with technical and industrial expertise to ensure seamless integration, whatever the equipment environment or operating requirements of the machine.
- Crouzet belongs to Custom Sensors & Technologies (CST) which is made up of the leading brands of Kavlico, Crydom as well as the former divisions of BEI Technologies, including Newall and Systron Donner. In addition to the Micro-control products in this brochure, CST also offers an extensive range of products and solutions in detection, control and motorisation. The result? Even better service and technical choice for our customers.



- Eco-design is central to the company's "Offer Creation Process", the aim of which is to design products and services that correspond as closely as possible to customers' requirements and reduce their environmental impact throughout their life cycle.
- Customer satisfaction will always be our prime objective. To this end, we rely on standards ISO 9001 and ISO14001 to ensure that our design, industrialisation, manufacturing and commercialisation processes correspond to our customers' requirements.

All Crouzet products are fully compliant with the RoHS directive



www.crouzet.com

► Expertise - for all your applications

- **Crouzet's Pneumatic expertise**

provides you with an offer to meet all your automation system requirements, including systems for explosive atmospheres.

The quality of the Pneumatic components is based on a rigorous organisation which meets all current European and international directives, standards and approvals.

- **All our products are fully compliant** with the RoHS directive and embody an eco-design concept.

- The Pneumatic offer is the result of the implementation of Crouzet applications and expertise:

- Listening to and analysing** your requirements
- Expertise** in the associated applications: mechanical, electronic, sensors, etc.
- Prototyping and industrialisation**
- Tests**
- Standardisation and certification** (IEC, EN, UL-CSA, ATEX, etc.)
- Equipment** which is responsive and effective
- International logistics** and after sales support.

- **Crouzet has developed broad expertise** in ensuring that your specific needs are taken into account. Thanks to this expertise, we are continuously developing our standard products to create solutions tailored to your requirements.

► Some relevant areas

Water treatment, chemical factories, silos, gas storage, ports, refineries, paper industry, paint factories, vehicles (if used in ATEX conditions), etc.



► Pneumatic offer for use in industrial and explosive atmospheres

► This guide has been designed to help you quickly identify the appropriate products for your requirements. Most of our pneumatic components are available in a standard range and a range for use in explosive atmospheres (ATEX): this information is given in the right-hand column on each page.

● Industrial range

The standard range of pneumatic components is designed to meet requirements for industrial applications.

The operating characteristics (pressure, flow rate, service life, etc.) have been optimised to best meet these needs.



● Range for use in explosive atmospheres

The range for use in explosive atmospheres has been developed specifically for applications requiring compliance with European Directive 94/9/EC, the full details of which can be found on pages 30 and 31 of this guide.

The user is responsible for ensuring the compliance of his installations. All new installations must be compliant, and replacements in the event of breakdown or maintenance must comply with this directive.



● Characteristics of our ATEX components

- ATEX products are specifically marked in accordance with the latest versions of harmonised standards
- Every product is supplied with a guide specifying the usage restrictions in explosive atmospheres
- A copy of the approval certificate can be provided if requested at the time of order
- The order entry must state the usage conditions Crouzet states the usage restrictions on acknowledgements of receipt of order, delivery notes and invoices



● Crouzet has produced a separate catalogue for Pneumatic products for use in explosive atmospheres.

This catalogue gives details of the entire Crouzet range of ATEX pneumatic products along with associated standards, certifications, directives, markings and order conditions.




► ATEX Directive 94/9/EC: general information

Principles of Directive 94/9/EC:

- The directive aims to harmonise the legislation of European Union member states in order to ensure free circulation of equipment intended for use in explosive atmospheres (gas and dust).
- Since 1 July 2003, this directive has applied to electrical, mechanical, hydraulic and pneumatic products.
- It concerns the assessment of protective devices and systems (manufacturers) as well as the design (design office), installation (installers, panel-builders) and maintenance (maintenance depts) of installations.

Definition of an explosive atmosphere:


- An explosive atmosphere is defined as a mixture of flammable substances (in the form of gas, vapour, mist or dust) with air under atmospheric conditions in which, after ignition, combustion spreads throughout the entire unburned mixture.



Some relevant areas:



Water treatment



Chemical factories



Silos



Gas storage



Ports

Refineries

Paper industry

Paint factories

Vehicles
(if used in ATEX conditions)

Equipment definition:

Equipment for surface industry - Group II

| Zone | 0 | 20 | 1 | 21 | 2 | 22 |
|--|--|----|--|----|---|----|
| Type of atmosphere G = Gas, D = Dust | G | D | G | D | G | D |
| Presence of Explosive atmosphere | Continuous presence (or for long periods, i.e. more than 1000 hours per year) | | Intermittent presence (or occasional, i.e. 10 to 1000 hours per year) | | Fleeting presence (or rare, i.e. 1 to 10 hours per year) | |
| Category of equipment that can be used as per 94/9/EC dated 23/03/94 | 1 | | 2 | | 3 | |

Marking example:

Certified products must incorporate marking specific to Directive 94/9/EC, such as:

Crouzet Automatismes SAS
 2 rue du Docteur Abel, 26902 Valence, FRANCE
 Type: 81513530
 Serial no:
 Year of construction
CE 0081 ⊕ II 1 G
Ex ia II C T6
LCIE 02 ATEX 6121 X
 Max. amb. T: +50°C

Explanation of the marking example:

- The CE marking along with the identification number of the notified body responsible for monitoring the QCS (0081 = LCIE).

CE 0081 ⊕ II 1 G

- The ⊕ symbol indicating that this product can be used in an explosive atmosphere followed by the equipment group (II = Surface Industries), the category (1 = continuous presence; 2 = intermittent presence; 3 = fleeting presence), and the type of explosive atmosphere G = Gas, D = Dust.

In affixing this CE marking, the manufacturer declares that the product has been manufactured in complete conformity with the requirements of all the relevant directives.

- Next line of the marking specified by the harmonised standards:

Ex ia II C T6 X

Reference to the operating instructions for the product

Temperature Class corresponding to a max. surface temperature of 85°C

Subdivision IIC: including hydrogen acetylene in particular, carbon bisulfur

Protection method used: intrinsic safety

Symbol indicating that the equipment complies with one or more protection methods

- The CE-Type Examination Certificate reference (if appropriate).

LCIE 02 ATEX 6121 X

Max. amb. T: +50°C

- The ambient operating temperature range.


In the event of use in an explosive atmosphere caused by dust, the following items are added to the marking:

- The surface limit temperature T° C for use in an explosive atmosphere caused by dust.


- The IP rating (only for dust)

► Examples of applications:


► Medical mattress



► Textile machine




► Industrial valve




Pneumatic actuators for quarter-turn or proportional taps and valves allow open/close commands and flow rate changes to be automated.
The pneumatic actuating cylinder is operated by means of an air distributor valve built into the valve body and controlled by a solenoid valve.


▷ Marking control system



▷ Semi-automatic resin filling system, with anti-drip control



▷ Automatic assembly system



► Particular realizations

► Component on manifold mastered



► Solenoid valves on manifold



► System for inflating



► Valves modules on manifold



For others configurations, consult us

General summary

Pages



Manual actuated valves

11



Position detectors

21



Pressure switches - Vacuum

35



Pneumatic logic components

41



Electro-pneumatic control valves

57



Multi-fluid solenoid valves


69




Teaching materials

72

Manual actuated valves



Push buttons diameter 12 and actuators



| Features | Actuator color | Valve color | Push button round | Push button double round |
|----------|----------------|-------------|-------------------|--------------------------|
| Version | NC black | black | 81 735 511 | — |
| | NC red | black | 81 735 512 | — |
| | NC black/red | black | — | 81 733 511 |
| | NO black | grey | 81 735 011 | — |
| NO | NO red | grey | — | — |
| | NO black/red | grey | — | — |

Symbol

NC





NO




Characteristics

| | | | |
|--|-------------------------|-----------------------|-----------------------|
| Operating pressure | bar | 2 → 8 | 2 → 8 |
| Orifice diameter | mm | 2.7 | 2.7 |
| Flow at 6 bars | Nl/mn. | 200 | 200 |
| Valves | NC : black NO : grey | ● | ● |
| Operating forces (depending on actuator) | N | 8 → 18 | 8 → 18 |
| Effective travel | mm | 1 | 1 |
| Fluid: dry or lubricated air | | ● | ● |
| Push-in connectors for semi-rigid tubing (NFE 49100) | mm | Ø 4 | Ø 4 |
| Operating temperature | °C | -5 → +50 | -5 → +50 |
| Mechanical life | operations | 1.5 x 10 ⁶ | 1.5 x 10 ⁶ |
| Weight | g | 35 | 40 |


Dimensions



Threaded barrel



2 threaded barrels





3-position lever
manual return

81 716 511

81 716 512

—

—

—



3-position lever
spring return


81 715 511

81 715 512

—

—

—



Horizontal outputs

81 280 510

—

—

—

—

Vertical outputs



81 281 510

—

—

—

—




| | |
|-----------------------|-----------------------|
| 2 → 8 | 2 → 8 |
| 2.7 | 2.7 |
| 200 | 200 |
| ● | ● |
| ● | ● |
| 8 → 18 | 8 → 18 |
| 1 | 1 |
| ● | ● |
| Ø 4 | Ø 4 |
| -5 → +50 | -5 → +50 |
| 1.5 x 10 ⁶ | 1.5 x 10 ⁶ |
| 65 | 65 |


| | |
|-----------------------|-----------------------|
| 2 → 8 | 2 → 8 |
| 2.7 | 2.7 |
| 200 | 200 |
| ● | ● |
| ● | ● |
| 8 → 18 | 8 → 18 |
| 1 | 1 |
| ● | ● |
| Ø 4 | Ø 4 |
| -5 → +50 | -5 → +50 |
| 1.5 x 10 ⁶ | 1.5 x 10 ⁶ |
| 65 | 65 |

| | |
|-----------------------|-----------------------|
| 2 → 8 | 2 → 8 |
| 2.7 | 2.7 |
| 200 | 200 |
| — | — |
| — | — |
| 1 | 1 |
| — | — |
| Ø 4 | Ø 4 |
| -5 → +50 | -5 → +50 |
| 1.5 x 10 ⁶ | 1.5 x 10 ⁶ |
| 14 | 14 |


81 715 - 81 716




Square lever



81 280 010 - 81 280 510



81 281 010 - 81 281 510




3/2 valves for manual actuators Ø 22 mm



| | | | | | | | | |
|--|----------------|------------|------------|------------|------------|------------|------------|------------|
| 3/2 valve supplied with screws for fixing the adaptor | Connection Ø 4 | 89 543 501 | 89 543 101 | — | — | — | — | — |
| Valve(s) 3/2 fixed on adaptor (supplied with adaptor not assembled) | Gas 1/8 | 89 543 701 | 89 543 201 | — | — | — | — | — |
| Adaptor for 3/2 valve on actuators Ø 22 | Connection Ø 4 | — | — | 89 543 105 | 89 543 005 | 89 543 305 | 89 543 205 | — |
| Version | NC | NO | NC | NO | NC + NO | NC + NC | — | 24 679 702 |

Symbol




Characteristics

| | | | | | | | | |
|----------------------------------|------------|-------------------|-------------------|-------------------|-------------------|-------------------|-------------------|----|
| Operating pressure | bar | 0 → 10 | 0 → 10 | 0 → 10 | 0 → 10 | 0 → 10 | 0 → 10 | — |
| Orifice diameter | mm | 2 | 2 | 2 | 2 | 2 | 2 | — |
| Flow at 4 bars | Nl/min | 90 | 90 | 90 | 90 | 90 | 90 | — |
| Control force | N | 12.6 | 12.6 | 12.6 | 12.6 | 12.6 | 12.6 | — |
| Operating temperature in dry air | °C | -10 → +60 | -10 → +60 | -10 → +60 | -10 → +60 | -10 → +60 | -10 → +60 | — |
| Life | operations | 1.5×10^6 | — |
| Non-connectable exhaust | | • | • | • | • | • | • | — |
| Weight | g | 50 | 50 | 60 | 60 | 110 | 110 | 40 |

Principle of operation

NC version




Dimensions

89 543 001 - 89 543 201


89 543 501 - 89 543 701

Ø 22 series




Holes drilled in panel for actuators Ø 22

EN 50007



Installation




* > 40 Ø 40 push-buttons
* > 45 for lever type rotary switches

Actuators Ø 22 mm for manually operated valves



| | | | | | | |
|-----------------------------|---------------------|-----------------------------|----------------------------------|----------------------------|----------------------------|------------------|
| Push buttons | Red 24 678 129 | Green 24 678 128 | Red 24 678 173 | Red 24 678 171 | — | — |
| 2-positions rotary switches | Black 24 678 127 | — | 24 678 172 | — | — | — |
| 3-positions rotary switches | — | — | — | — | 24 678 174 | 24 678 175 |
| Function | Flush push contact | Emergency stop plastic Ø 40 | Emergency stop Ø 40 mm push-turn | Black symmetrical actuator | Black symmetrical actuator | Long lever Black |

Symbol



Position



| | | | | | | |
|--------|---|----|----|----|----|----|
| Weight | g | 30 | 45 | 45 | 45 | 45 |
|--------|---|----|----|----|----|----|

| | |
|------------|---------------------------------------|
| Dimensions | 24 678 127 - 24 678 128 24 678 129 |
| | 24 678 171 - 24 678 172 24 678 173 |



| | | | | | | | | |
|-----------------------------|------------|---------------------------------------|----------------------------|--|------------------|------------------------------------|-----------------------------------|---------------------------------------|
| 2-positions rotary switches | 24 678 180 | — | 24 678 176 | 24 678 178 | 24 678 177 | 24 678 179 | 24 678 182 | 24 678 181 |
| 3-positions rotary switches | — | RONIS key 455 removable in position 0 | Black symmetrical actuator | Black symmetrical actuator with return | Long lever Black | Black Long lever, spring to center | RONIS key 455 remov. in pos. 0 | RONIS key 455 removable in position 0 |
| Function | — | — | — | — | — | — | 3 positions with spring to center | 3 fixed positions |

Symbol



Position



| | | | | | | | |
|--------|----|----|----|----|----|----|----|
| Weight | 70 | 45 | 45 | 16 | 45 | 70 | 70 |
|--------|----|----|----|----|----|----|----|

| | | | |
|------------|---------------------------------------|---------------------------------------|---------------------------------------|
| Dimensions | 24 678 174 - 24 678 176 24 678 178 | 24 678 175 - 24 678 177 24 678 179 | 24 678 180 - 24 678 181 24 678 182 |
| | 24 678 178 | 24 678 179 | 24 678 182 |

Pneumatic 2-hand control

Conforms to the
Machinery Directive



Definition (conforming to EN 574 +A1)

A pneumatic 2-hand control device is used with dangerous machinery and requires the simultaneous use of both hands to trigger and maintain machine operation. Such a device must be located outside the dangerous zone, so that the operator cannot enter this zone before the machine has come to a complete standstill.

A pneumatic 2-hand control device is composed of 2 parts :

- 2 manual pushbuttons which require the simultaneous use of both hands.
- A pneumatic relay.

1

Types of 2-hand control devices

| Requirements | Type | | | | |
|--|------|----|-----|---|---|
| | I | II | III | | |
| | | | A | B | C |
| Use of both hands (simultaneous actuation) | ● | ● | ● | ● | ● |
| Relationship between input signals and output signal | ● | ● | ● | ● | ● |
| Cessation of the output signal | ● | ● | ● | ● | ● |
| Prevention of accidental operation | ● | ● | ● | ● | ● |
| Prevention of defeat | ● | ● | ● | ● | ● |
| Reinitiation of the output signal | | ● | ● | ● | ● |
| Synchronous actuation | | | ● | ● | ● |
| Use of category 1 (EN 954-1) | ● | | ● | | |
| Use of category 3 (EN 954-1) | | ● | | ● | |
| Use of category 4 (EN 954-1) | | | | | ● |

Category 1 (EN ISO 13849) : the system should use well tried components and principles.

Category 3 (EN ISO 13849) : the system must be designed so that a single fault will not cause the loss of the safety function.

Category 4 (EN ISO 13849): the system must be designed so that an accumulation of faults must not lead to a loss of the safety function.

Synchronous action

An output signal is only generated if both control actuating devices are actuated within 500 ms.

Resetting the output signal

The release of a single control device interrupts the output signal, but a reset is only possible once both control devices have been released.

Pneumatic relay for two-hand control

- 100% pneumatic
- Complies with Machinery Directive and the standard EN 574 +A1
- CE Certification type-III A and III B





Pneumatic relay for two-hand control
EN 574 +A1 classification

81 580 101
III A

81 580 202
III B

Symbol




Characteristics

| | | | |
|----------------------------------|------------|---------------------|-----------------------------------|
| Operating pressure | bar | 2 → 8 | 2 → 8 |
| Orifice diameter | mm | 2.5 | 2.5 |
| Max. delay between input signals | s | 0.2 max. | 0.2 max. |
| Connection | | Sub-base 81 532 001 | Semi-rigid tubing Ø 4 (NFE 49100) |
| Operating temperature | °C | -5 → +50 | -5 → +50 |
| Mechanical life | operations | 10 ⁷ | 10 ⁷ |
| Weight | g | 90 | 320 |


Principle of operation

81 580 101




Connections (Typical application with double-acting cylinder)

81 580 101



Components follow current standards


81 580 202



To obtain an output signal it is necessary to give simultaneous input signals 'a' and 'b' with a max. delay of 0.45. The output signal 's' is lost if one or both of the inputs are removed.


Dimensions

81 580 101



Mounted on sub-base 81 532 001
(See page 55 of Pneumatic catalogue)

81 580 202



Two-hand pneumatic safety start module

- Conforms to the Machinery Directive and standard EN 574
- Including pneumatic relay to classification IIIA or IIIB depending on version





Two-hand pneumatic safety start module
Pneumatic relay (to EN 574)

81 580 504
Type III A

81 580 503
Type III B


Symbol




Characteristics

| | | | |
|----------------------------------|------------|-----------------------------------|-----------------------------------|
| Operating pressure | bar | 2 → 8 | 2 → 8 |
| Orifice diameter | mm | 2.5 | 2.5 |
| Max. delay between input signals | s | 0.2 max. | 0.2 max. |
| Connection | | Semi-rigid tubing Ø 4 (NFE 49100) | Semi-rigid tubing Ø 4 (NFE 49100) |
| Operating temperature | °C | -5 → +50 | -5 → +50 |
| Mechanical life | operations | 1.5×10^6 | 1.5×10^6 |
| Weight | g | 1000 | 1410 |

Connections (Typical application with double-acting cylinder)
81 580 504




81 580 503




Components follow current standards

Dimensions

81 580 503 - 81 580 504



Fixing viewed from below




Pneumatic impulse counters

- 4, 5, 6 digits with or without reset
- With or without pre-selection



| Totalizer | 99 766 001 | 99 766 002 | 89 538 201 |
|----------------------|---------------------------|---------------------------------|--|
| Preselection counter | — | — | — |
| Version | 6 digits no reset to zero | 4 digits with manual zero reset | 5 digits with manual or pneumatic zero reset |


Symbol



Characteristics

| | | | | |
|---------------------------------------|---------|---------|---------|--------|
| Supply pressure | bar | 2 → 8 | 2 → 8 | 2 → 8 |
| Pressure to break | bar | > 0.3 | > 0.3 | > 0.15 |
| Pressure to make | bar | > 1.4 | > 1.4 | > 0.8 |
| Reset : Minimum pressure | bar | — | — | 2 |
| Reset time | ms | — | — | 150 |
| Circuit pressure bar | bar | — | — | 2 → 8 |
| Signal emitted when preset is reached | 0 → +60 | 0 → +60 | 0 → +60 | • |
| Operating temperature °C | 150 | 150 | 136 | |
| Weight - | g | | | |

Connection




A - Output signal
P - Supply
Y - 'Reset to zero' signal
Z - Input signal

Note : the count pulse must be removed before the reset pulse is applied. The preset value can be changed during operation without the counter resetting to zero.


Dimensions

Connectors for semi-rigid tubing Ø 4 (NFE 49100)


99 766 002



99 766 001



89 538 201




Indicators and pedal valves

■ Ergonomics



Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Pneumatic indicators Ø 22

Red

84 150 201

Green

84 150 202

Yellow

84 150 203

Blue


84 150 204

Pedal valve - Version NC

—

81 999 501

Symbol




Characteristics


| | | | |
|---|------------|-----------------|-----------------------|
| Operating pressure | bar | 2 → 8 | — |
| Push-in connection for semi-rigid tubing (NFE 49100) | mm | Ø4 | Ø4 |
| Operating temperature | °C | -5 → +50 | -5 → +50 |
| Mechanical life | operations | 10 ⁷ | 1.5 × 10 ⁶ |
| Weight | g | 34 | 290 |

Dimensions



84 150 201 - 84 150 202
84 150 203 - 84 150 204



81 999 501




Holes drilled for indicators



ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Position detectors



Pressure decay sensor

■ 100 % pneumatic




Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Pressure decay sensor

81 504 025

Symbol




Characteristics


| | | |
|-------------------------------------|------------|---------------------|
| Operating pressure | bar | 2 → 8 |
| Flow at 6 bars | Nl/min | 200 |
| Tripping point with 6 bar supply | b | 0.3 |
| Connection | | Sub-base page 54-55 |
| Operating temperature | °C | -5 → +50 |
| Mechanical life | operations | ≥10 ⁷ |
| Weight | g | 25 |

Connections

Without flow restrictor



With flow restrictor




Principle of operation

Fitted in-line between the cylinder and the control valve, the sensor will give an output when the pressure in this line is exhausted and the cylinder is at end of stroke.


For the correct usage of sensors on a falling pressure, it is recommended that the practical cylinder load is limited to 60% of the theoretical force.

Evolution of pressure within a double-acting cylinder



Dimensions

81 504 025



ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Low force position detector

- 100 % pneumatic
- Conforme à la norme DIN 41365 Forme A
- Faible effort d'actionnement < 50 g à 6 bars
- Pas de consommation permanente d'air comprimé



Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Function


NO

NC

81 290 501

81 290 001

Symbol




Characteristics


| | | |
|--|-------------------|-------------------|
| Orifice diameter mm | 2 | 2 |
| Operating pressure bar | 3 → 8 | 3 → 8 |
| Flow at 4 bars Nl/min | 100 | 100 |
| Activation force at 6 bars N | < 0,5 | < 0,5 |
| Permissible fluids (air / inert gas) | | |
| Max/min of fluid temperatures operating °C | -10 → +50 | -10 → +50 |
| temperatures storage °C | -10 → +60 | -10 → +60 |
| Mechanical life at 6 bars operation | > 10 ⁷ | > 10 ⁷ |
| Response time on activation ms | ≤ 15 | ≤ 15 |
| time on release ms | ≤ 15 | ≤ 15 |
| Barb connection for semi-rigid tubing | 2.7 x 4 | 2.7 x 4 |
| Weight g | 8.5 | 8.5 |

Principle of operation NC

Desactivated




Activated




Operation accessories

Unless otherwise requested, flat and roller-ended levers are supplied loose.

161 A
flat R 25.4
70 507 524




161 E
with roller R 24.1
70 507 529




Dimensions


DIN 41635 Form A



161 A
R 25.4 ±0,2




161 E
R 24.1 ±0,2



ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com




"Microvalve" series position detectors






| | | | | |
|----------|----------|--------------------------|--------------------------|--------------------------|
| Version | NO NC | 81 280 010 81 280 510 | 81 281 010 81 281 510 | — |
| Features | | Horizontal output | Vertical output | Rear connection by screw |

Symbol

NO




NC



Characteristics

| | | | | |
|--|---------|---------------------|---------------------|---------------------|
| Operating pressure | bar | 2 → 8 | 2 → 8 | 2 → 8 |
| Orifice diameter | mm | 2.7 | 2.7 | 2.7 |
| Flow at 6 bars | Nl/min | 200 | 200 | 138 |
| Operating force at 6 bars | N | 15 | 15 | 15 |
| Effective travel | mm | 1 | 1 | 1 |
| Push-in connection for semi-rigid tubing (NFE 49100) | mm | Ø 4 | Ø 4 | Ø 4 |
| Operating temperature | °C | -5 → +50 | -5 → +50 | -5 → +50 |
| Mechanical life | operat. | 5 x 10 ⁶ | 5 x 10 ⁶ | 5 x 10 ⁶ |
| Weight | g | 14 | 14 | 20 |


Principle of operation




Actuation positions :

PFC : End of travel position
PA : Operating position (max output kV)
PRT : Release position (max. exhaust kV)
PR : Rest position

NC




NO




Dimensions


81 281 010 - 81 281 510







81 280 010 - 81 280 510



81 283 510





“Microvalve” series position detectors



| Features | Short lever | With ball | Roller trip | With roller | Threaded barrel Ø 16 Plunger |
|----------|-------------|-----------------|-------------|-------------|---------------------------------|
| Version | NC | Vertical output | | | |
| | 81 281 502 | 81 281 504 | 81 281 508 | 81 281 509 | 81 737 501 |

Symbol




Characteristics


| | | | | | |
|--|---------|---------------------|---------------------|---------------------|---------------------|
| Operating pressure | bar | 2 → 8 | 2 → 8 | 2 → 8 | 2 → 8 |
| Orifice diameter | mm | 2.7 | 2.7 | 2.7 | 2.7 |
| Flow at 6 bars | Nl/min | 200 | 200 | 200 | 200 |
| Operating force at 6 bars | N | 15 | 15 | 15 | 25 |
| Effective travel | mm | 1 | 1 | 1 | 1 |
| Push-in connection for semi-rigid tubing (NFE 49100) | mm | Ø 4 | Ø 4 | Ø 4 | Ø 4 |
| Operating temperature | °C | -5 → +50 | -5 → +50 | -5 → +50 | -5 → +50 |
| Mechanical life | operat. | 5 x 10 ⁶ |
| Weight | g | 16 | 18 | 18 | 90 |

Dimensions


81 281 502




81 281 504




81 281 508



81 281 509




81 737 501



Actuation positions :

PR : Rest position


"Miniature" series position detectors



Part numbers

| | | | | | |
|---------|---|-------------------|---------------------------|---------------------------|--|
| Version | Push-in connection for semi-rigid tubing (NFE 49100) | 81 921 501 | 81 921 701 | 81 921 702 | 81 921 707 |
| NC | Ø 4 silenced exhaust | — | — | — | — |
| | M5 connectable exhaust | — | — | — | — |
| | Ø 4 connectable exhaust * | — | — | — | — |
| | Ø 6 connectable exhaust * | — | — | — | — |
| NO | Ø 4 silenced exhaust | — | — | — | — |
| | Ø 6 silenced exhaust | — | — | — | — |
| Control | | Simple plunger | Lever with plastic roller | Lever with roller bearing | Lever with one-way trip plastic roller |


Symbol



Characteristics

| | | | | | |
|---------------------------|------------|------------------|------------------|------------------|------------------|
| Operating pressure | bar | 0.1 → 8 | 0.1 → 8 | 0.1 → 8 | 0.1 → 8 |
| Orifice diameter | mm | 2.7 | 2.7 | 2.7 | 2.7 |
| Flow at 6 bars | Nl/min | 200 | 200 | 200 | 200 |
| Actuation force at 6 bars | N | 18 | 18 | 18 | 18 |
| Circuit function : NC | | ● | ● | ● | ● |
| Circuit function: NO | | — | — | — | — |
| Connectable exhaust | | | | | |
| Operating temperature | °C | -5 → +50 | -5 → +50 | -5 → +50 | -5 → +50 |
| Mechanical life | operations | ≥10 ⁷ | ≥10 ⁷ | ≥10 ⁷ | ≥10 ⁷ |
| Weight | g | 62 | 75 | 80 | 77 |


Principle of operation



Actuation travel

Vertical attack

Simple plunger




Actuation positions :


- PA : Operating position (max output KV)
- PFC : End of travel position
- PO : Mid-position closed (no exhaust, no outlet)
- PRT : Release position (max exhaust KV)
- PR : Rest position

Dimensions


81 921 501



81 921 701 - 81 921 702




81 921 707



* with barb for tube Ø 2.7 x 4

Material: body zamak



81 921 806

Lever with plastic roller

81 921 714

Lever with roller bearing

81 921 719

81 921 911

81 921 901




Lever with plastic roller

81 921 717

81 921 912

81 921 902

Lever with roller bearing



0.1 → 8
2.7
200
18

0.1 → 8
2.7
200
18

0.1 → 8
2.7
200
18

0.1 → 8
2.7
200
18


•
—
-5 → +50
≥10⁷
75

•
—
-5 → +50
≥10⁷
80

•
—
-5 → +50
≥10⁷
100

•
—
-5 → +50
≥10⁷
100

With lever





Horizontal actuating 30° cam (other angles of attack are also possible, 45° even 90°).


With lever

With lever


One-way trip lever



81 921 806




81 921 714



81 921 717 - 81 921 719

81 921 901 - 81 921 902


81 921 911 - 81 921 912



Material: body zamak

Other configuration on demand

"Compact" series position detectors




- 100 % pneumatic
- All metal



Part numbers

| | | | | |
|----------|---------------------------------------|--|--|--|
| Features | Direct acting 81 922 401 | Rotary actuator 81 922 205 | Rotary actuator 81 922 010 | Rotary actuator 81 922 210 |
| Version | Roller plunger with unthreaded barrel | Right-hand rotary head with roller lever (CNOMO) | Programmable rotary head without lever | Programmable rotary head without lever |

Symbol




Characteristics

| Connection | BSP push-in for semi-rigid tubing (NFE 49100) | mm | Ø 4 | 1/8 | Ø 4 | 1/8 |
|---------------------------------------|---|-------------------|-------------------|-------------------|-------------------|-------------------|
| Operating pressure | bar | 0.1 → 8 | 0.1 → 8 | 0.1 → 8 | 0.1 → 8 | 0.1 → 8 |
| Bore diameter | mm | 3 | 3 | 3 | 3 | 3 |
| Flow at 6 bars | Nm ³ /h | 200 | 200 | 200 | 200 | 200 |
| Activation force at 6 bars | daN | 2.5 | 2.5 | 2.5 | 2.5 | 2.5 |
| Circuit function: NC | | ● | ● | ● | ● | ● |
| Mechanical life | operations | > 10 ⁷ |
| Silenced or connectable (1/8) exhaust | | ● | ● | ● | ● | ● |
| Operating temperature | °C | -5 → +50 | -5 → +50 | -5 → +50 | -5 → +50 | -5 → +50 |
| Weight | g | 150 | 193 | 175 | 175 | 175 |

Accessories


| | | | | | | |
|------------------------------|--------------------|--|---|---|---|---|
| Lever with roller | plastic bearing | 79 452 103 79 452 104 | — | ● | ● | ● |
| Lever with adjustable roller | plastic bearing | 79 452 123 79 452 124 | — | ● | ● | ● |
| Adjustable steel rod lever | | 79 452 133 | — | ● | ● | ● |

Principle of operation



Vertical attack

Detectors with roller plunger with unthreaded barrel.



Actuation positions :

- PA : Operating position (max output kV)
- PFC : End of travel position
- PO : Mid-position closed (no exhaust, no outlet)
- PRT : Release position (max exhaust kV)
- PR : Rest position


The detectors 81 922 010 and 81 922 210 can operate to both left and right.

Material: body zamak

Other configuration on demand

Horizontal attack



Detectors with roller plunger with unthreaded barrel.



Rotary actuator


Detectors with levers

81 922 - 81 922 0 - 81 922 2




Dimensions


81 922 401




81 922 205 - 81 922 0 - 81 922 2
79 452 103 - 79 452 104



79 452 123 - 79 452 124




79 452 133



"Adjustable stop" series position detectors

- 100 % pneumatic
- All metal



Part numbers

Push-in connection for semi-rigid tubing (NFE 49100)



81 923 001

Barb for tube 2.7 x 4

81 921 505

Push-in connector for tube Ø 4



Symbol



Characteristics

| | | | |
|--|------------|------------------|------------------|
| Operating pressure | bar | 0,1 → 8 | 0,1 → 8 |
| Orifice diameter | mm | 2 | 2,7 |
| Flow at 6 bars | NI/min | 130 | 200 |
| Actuation force at 6 bars | N | 16 | 21 |
| Circuit function: NC | | ● | ● |
| Max. load: without shock | daN | 1000 | 1000 |
| Will stop a 63 mm Ø cylinder : 6 bar supply | | ● | ● |
| Operating temperature | °C | -5 → +50 | -5 → +50 |
| Mechanical life | operations | ≥10 ⁷ | ≥10 ⁷ |
| Weight | g | 27 | 90 |
| Actuation positions | | | |
| PA : Operating position (max output kV) | mm | 0,4 | 0,7 |
| PFC : End of travel position | mm | 0 | 0 |
| PO : Mid-point closed (no exhaust, no outlet) | mm | 0,9 | 1 |
| PRT : Release position (max. exhaust kV) | mm | 1,5 | 1,5 |
| PR : Rest position | mm | 3 | 3 |

Principle of operation




| Versions | PO | PA | PFC | PRT | PR |
|-----------|-----|-----|-----|-----|----|
| With barb | 0.9 | 0.4 | 0 | 1.5 | 3 |
| Ø 4 | 1 | 0.7 | 0 | 1.5 | 3 |

Values in mm


Actuation positions :
 PA : Operating position (max output kV)
 PFC : End of travel position
 PO : Mid-position closed
 (no exhaust, no outlet)
 PRT : Release position
 (max exhaust kV)
 PR : Rest position

Dimensions

81 923 001




81 921 505



Fixing


This should be as close as possible to the plunger



Material: body zamak

Position detectors use with relay

- 100 % pneumatic
- All metal
- Low force operation < N 1
- Very low force Version 30 mN



References

Version




81 512 201
with ball

81 512 401
with wire

81 502 435
Positive

81 505 435
Negative

Symbol



Characteristics

Push-in connection for semi-rigid tubing (NFE 49100)

mm

Ø 4

Ø 4

Life at 6 bars

operations

10^7

10^7

Actuation force at 6 bars

N

0,8

0,025

Fluid used: that delivered by the leak sensor relay..

•

•

Operating temperature

°C

-5 → +50

-5 → +50

Weight

g

24,5

23,5

Operating pressure

bar

2 → 8

2 → 8

Sensor consumption for relay supply at 6 bar

Nl/l

5

5

The distance between relay and sensor must be less than 15 m for a tube Ø 2.7 x 4 mm

Connection - sub-base see pages 54/55

Mechanical life


operations

$\geq 10^7$

$\geq 10^7$

$\geq 10^7$


Connection




Principle of operation

Supplied at industrial pressure, the relay produces a permanent bleed at its input port.

A sensor shutting off this bleed causes the relay to switch.




81 502 435




Dimensions


81 512 201



81 512 401



81 502 435 - 81 505 435



Material: brass

Position detectors


- 100 % pneumatic
- All metal
- Gap, proximity, paddle



Part numbers

| Detector | 81 371 401 de proximité | 81 372 201 gap | 81 372 401 gap | 81 372 901 with palette |
|----------|----------------------------|-------------------|-------------------|----------------------------|
|----------|----------------------------|-------------------|-------------------|----------------------------|


Symbol




Characteristics

| | | | | | |
|---|------------------|-------------------------|------------|------------|-----------|
| Detection distance | mm | 6 → 10 | 18 | 100 | — |
| 18 mm gap sensor | — | — | — | — | — |
| Supply pressure | bar | 0.5 → 2.5 | 0.5 → 2.5 | 0.5 → 2.5 | — |
| Minimum output pressure | mbar | 1 | 5 | 5 | — |
| Unlimited life (static component) | — | • | • | • | — |
| Operating temperature | °C | - 20 → +70 | - 20 → +70 | - 20 → +70 | — |
| Consumption at supply pressure of: | Nl/h | 800 | 100 | 700 | — |
| 2.5 b | Nl/h | 2500 | 2200 | 700 | — |
| Barb connection for semi-rigid tubing (NFE 49100) | mm | Ø 2.7 x 4 | Ø 2.7 x 4 | Ø 2.7 x 4 | Ø 2.7 x 4 |
| Operating pressure | nozzle sensor | d. detection 200 mm bar | — | — | 2 → 8 |
| | | d. detection 100 mm bar | — | — | 2 → 8 |
| Flow | nozzle at 2 bars | Nl/h | — | — | 1 → 4 |
| | sensor at 2 bars | Nl/h | — | — | 320 |
| | at 2 bars | N | — | — | 320 |
| | at 6 bars | N | — | — | 0.03 |
| Sensor consumption for relay supply at 6 bars | Nl/min | — | — | — | 0.09 |
| Weight | g | 36 | 9 | 63 | 14 |


Principle of operation



Connection



Encombrements



Amplifiers for mounting on installation plan

■ Gap sensor



Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Part numbers

Simple amplifiers (for 81 372 201/401)

81 502 230

81 505 230

Sensitive amplifiers (for 81 371 401)

81 502 320

81 505 320

Version



positive

negative

positive

negative

Symbol





Characteristics

| | | | | | |
|---|------------|-----------------|-----------------|-----------------|-----------------|
| Pressure to make | mb | 10 → 20 | 10 → 20 | 1 → 4 | 1 → 4 |
| Operating pressure (non-lubricated air) | bar | 2 → 8 | 2 → 8 | 2 → 6 | 2 → 6 |
| Orifice diameter | mm | 2.5 | 2.5 | 2.5 | 2.5 |
| Average consumption at 4 bars | Nl/min | 5 | 5 | 5 | 5 |
| Permissible overload for 1 hour | mb | 800 | 800 | 800 | 800 |
| Operating temperature | °C | -5 → +50 | -5 → +50 | -5 → +50 | -5 → +50 |
| Mechanical life | operations | 3×10^6 | 3×10^6 | 3×10^6 | 3×10^6 |
| Weight | g | 150 | 150 | 185 | 185 |

Connections

Used for gaps up to 25 mm.


The supply to the sensor should be made via a pressure regulator or one-way flow restrictor (see page 52)
Connection - sub-base



Principle of operation

Simple amplifiers

An output at normal industrial pressure is delivered on a low pressure input.
NB: Hysteresis is 20% of the pilot pressure.





81 502 230

81 505 230

Positive output


Negative output

1- pilot
2- supply
3- output



Sensitive amplifiers

An output at normal industrial pressure is delivered on a very low pressure input.





81 502 320

81 505 320

Positive output


Negative output

Note: The specifications are given for a supply pressure of 6 bars, and for detection at the mid-point of the gap.





Dimensions

81 502 238 - 81 505 231



81 502 322 - 81 505 321



Other information

With gap sensors, use an amplifier with negative output if you require a signal on interruption of the jet.

ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Amplifier with intégral régulateur, positive output

- Setting Flow
- Fixing rail 35mm wide



Part numbers


Amplifiers with integral regulator

81 510 001

Version

Positive output

Symbol




Characteristics

| | | | | |
|--|--------------------------|-------------------|-------------------|-------------------|
| Pressure to make | mb | 0.5 → 1.5 | — | — |
| Reduced pressure supplied at port 8 | bar | 0.5 → 2.5 | — | — |
| Flow through port 8 | Nm³/h | 0.1 → 2.5 | — | — |
| Consumption of amplifier only | Nl/h | 100 → 200 | — | — |
| Permissible overload for 1 hour | mb | 300 | — | — |
| Operating temperature | °C | -5 → +50 | -5 → +50 | -5 → +50 |
| Mechanical life | operations | 3 x 10⁶ | 3 x 10⁶ | 3 x 10⁶ |
| Weight | g | 380 | — | — |
| Detectors (see page 28) | | | | |
| Nominal range | mm | Proximity Ø 12 | Proximity Ø 12 | Proximity Ø 12 |
| Min. total consumption for detection (0.5 b regulated pressure) | | 81 371 401 | 81 372 201 | 81 372 401 |
| Max. total consumption for short response time (2.5 b regulated pressure) | Nl/h | 880 | 140 | — |
| Min. detectable | Nl/h | 2750 | 400 | 920 |
| dimensions | nominal sensing distance | mm Ø 3 | Ø 2 - Ø 1.5 | Ø 7 - Ø 6.5 |
| Max. frequency of use | 2 | 2 | — | — |
| Force exerted by the jet on the parts to be detected | Hz | 5 | 5 | 5 |
| | N | 0.02 → 0.7 | 0.01 → 0.03 | 0.1 |

Connection


To use with detectors page 32

Principle of operation




Dimensions


Push-in connection for semi-rigid tubing Ø 4 mm (NFE 49100)




Viewed from B



Viewed from A



Pressure switches - Vacuum



Pressure switches - vacuum (electrical output)


- Conform to the Low Voltage Directive
- Can be used without enclosure according to IEC 664-1 pollution group III



Part numbers

| Pressure and vacuum switches | 81 513 552 | 81 513 502 | 81 513 501 | 81 513 522 |
|------------------------------|---------------|------------------|----------------------|----------------|
| Mounting | DIN rail | DIN rail | DIN rail | DIN rail |
| Actuators | Pressure with | Pressure without | Low pressure without | Vacuum without |
| Manual override | | | | |

Symbol



Characteristics

| | | | | | |
|--|--|------------------------|------------------------|-----------------------|-----------------------|
| Pneumatic connection | Push-in connection for semi-rigid tubing (NFE 49100) Tapped BSP via connector | Ø 4 ext. | Ø 4 ext. | Ø 4 ext. | Ø 4 ext. |
| Protection | IEC 529 | IP 20 | IP 20 | IP 20 | IP 20 |
| Permissible fluid: air, inert gases and liquids | | ● | ● | ● | ● |
| Adjustment of switching pressure (* adjusted to 0.3) | bar | 2 → 8 | 2 → 8 | 0.3 → 1.2 * | -0.3 → -0.8 |
| Hysteresis | at 1 bar at 2 bars at 4 bars at 6 bars max. 200 mb max. 250 mb | 0.5 0.6 0.8 1 | 0.5 0.6 0.8 1 | — — — ● — | — — — — ● |
| Pressure to break | | — | — | — | — |
| Mechanical life (operations) | | 10 ⁶ | 10 ⁶ | 10 ⁶ | 10 ⁶ |
| Contact rating (V resistive) | 5A - 220-230 V | 5A - 220-230 V | 5A - 220-230 V | 5A - 220-230 V | 5A - 220-230 V |
| Wire cross-section | mm ² | 0.75 | 0.75 | 0.75 | 0.75 |
| Operating temperature | °C | -10 → +70 | -10 → +70 | -10 → +70 | -10 → +70 |
| Weight | g | 48 | 46 | 46 | 46 |
| Standard electrical contact | | V4 83 170 4 I W2 | V4 83 170 4 I W2 | V4 83 170 4 I W2 | V4 83 170 4 I W2 |
| UL and cUL approval | | MH15213 (R) | MH15213 (R) | MH15213 (R) | MH15213 (R) |



Operation

Pressure operated

Vacuum operated

Electrical life

(Crouzet microswitch "V4" ref 83 170 4-1-W2)




For continuous vacuum applications, please consult us.


Other information

On request :

- Microswitch V4 ref. 83 170 0 i W2 high current
- Microswitch V4 ref. 83 170 9 i W2 low current




| 81 513 516 | 81 513 510 | 81 513 527 | 81 513 533 | 81 513 523 | 81 509 080 | 81 509 085 |
|---------------------------|---------------------------|---------------------------|---------------------|-------------------|---------------------------|---------------------------|
| Base mounted page 4/14 | Base mounted page 4/14 | Base mounted page 4/14 | 2 screws M4 | 2 screws M4 | Base mounted page 4/14 | Base mounted page 4/14 |
| Pressure without | Pressure with | Vacuum without | Pressure without | Vacuum without | Pressure without | Pressure with |



| | | | | | | | |
|------------------|------------------|------------------|------------------|------------------|---|-----------------|-----------------|
| Ø 4 ext. | Ø 4 ext. | Ø 4 ext. | — | — | — | Via sub-base | Via sub-base |
| — | — | — | 1/8 BSP | 1/8 BSP | — | IP 54 | IP 54 |
| IP 54 | — | • | • |
| ● | ● | ● | 2 → 8 | 2 → 8 | — | 1.4 ± 0.5 | 1.4 ± 0.5 |
| 2 → 8 | 2 → 8 | -0.3 → -0.9 | 0.5 | -0.3 → -0.8 | — | — | — |
| 0.5 | 0.5 | — | 0.6 | — | — | — | — |
| 0.6 | 0.6 | — | 0.8 | — | — | — | — |
| 0.8 | 0.8 | — | 1 | — | — | — | — |
| 1 | 1 | — | — | — | — | — | — |
| — | — | — | — | — | — | — | — |
| — | — | ● | — | ● | — | — | — |
| — | — | — | — | — | — | 0.6 ± 0.2 | 0.6 ± 0.2 |
| 10 ⁶ | — | 10 ⁶ | 10 ⁶ |
| 5A - 220-230 V | — | 5A - 220-230 V | 5A - 220-230 V |
| 0.75 | 0.75 | 0.75 | 0.75 | 0.75 | — | 1.5 | 1.5 |
| -10 → +70 | -10 → +70 | -10 → +70 | -10 → +70 | -10 → +70 | — | -10 → +70 | -10 → +70 |
| 56 | 58 | 56 | 65 | 65 | — | 80 | 80 |
| V4 83 170 4 I W2 | — | 83 133 004 | 83 133 004 |
| MH15213 (R) | — | — | — |

Electrical connections

81 513 501 - 81 513 502
81 513 522 - 81 513 552



81 513 510
81 513 516 - 81 513 527



Dimensions


81 513 552 - 81 513 502
81 513 501 - 81 513 522

Pressure switch with connector


81 513 516 - 81 513 510
81 513 527

81 516 082

81 513 533
81 513 523



81 509 080 - 81 509 085



Adjustable pressure switches (manostats) (pneumatic output)

■ 100 % pneumatic



Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Part numbers (and adjustment ranges)

| | | | | |
|------------------|---------------------------------------|---|---|--|
| Adjustment range | 50 → 500 mb 0.1 → 2.5 b 2 → 8 b | 81 505 140 81 505 150 81 505 160 | 81 502 140 81 502 150 81 502 160 | |
| Version | | Positive output | Negative output | |
| Accuracy | 50 → 500 mb 0.1 → 2.5 b 2 → 8 b | 10 % 4 % 4 % | 10 % 4 % 4 % | |

Symbol




Characteristics

| | | | | |
|-----------------------------------|---------------------------------------|---------------------------|---------------------------|--|
| Orifice diameter | mm | 2.5 | 2.5 | |
| Flow at 4 bars | l/min | 170 | 170 | |
| Hysteresis | 50 → 500 mb 0.1 → 2.5 b 2 → 8 b | 60 mb 100 mb 320 mb | 60 mb 100 mb 320 mb | |
| Connection - sub-base pages 54/55 | | • | • | |
| Operating temperature | °C | -5 → +50 | -5 → +50 | |
| Mechanical life | operations | 3×10^6 | 3×10^6 | |
| Weight | g | 160 | 160 | |

Connections


Example of pressure threshold adjustment
(mini-regulator - manostat)




Principle of operation

The manostats provide an on or off output signal when the input signal reaches a predetermined pressure threshold.

Positive output




Negative output



Dimensions


81 502 140 - 81 502 150 - 81 502 160
81 505 140 - 81 505 150 - 81 505 160




Other information Pressure switches with electrical output on request.

ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Adjustable vacuum switches (vacuostat)



- 100 % pneumatic
- For vacuum $-0,1 \rightarrow -0,9$ Bar






Part numbers

81 505 110
Positive output

81 502 110
Negative output

81 508 110
Electrical output

Symbol




Characteristics

| | | | | |
|-----------------------------------|------------|-------------------------|-------------------------|-------------------------|
| Adjustment range | b | $-0,1 \rightarrow -0,9$ | $-0,1 \rightarrow -0,9$ | $-0,1 \rightarrow -0,9$ |
| Flow at 6 bars | Nl/min | 170 | 170 | 170 |
| Hysteresis | mb | 80 | 80 | 80 |
| Connection - sub-base pages 54/55 | | • | • | • |
| Operating temperature | °C | $-5 \rightarrow +50$ | $-5 \rightarrow +50$ | $-5 \rightarrow +50$ |
| Mechanical life | operations | 3×10^6 | 3×10^6 | 3×10^6 |
| Weight | g | 160 | 160 | 180 |

Connections


Example of use:
Vacuum handling (vacuum generator,
vacuum pad, vacuostats).




Principle of operation

Vacuostats provide an on or off output signal when the input signal reaches a predetermined pressure threshold.

Positive output




Negative output




Dimensions

81 502 110 - 81 505 110



81 508 110



Vacuum handling components

- Sur le principe du Venturi
- Facilement raccordable




Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Part numbers


| | | | |
|-------------------|-------------------|-------------------|-------------------|
| Vacuum generators | 81 535 301 | 81 545 001 | 81 545 005 |
| | Sub-base mounting | Plug-in | Plug-in |



Characteristics

| | | | | |
|--|----------------------------|-------|--------|--------|
| Push-in connectors for semi-rigid tubing (NFE 49100) | Male/Female/Female (MFF) | — | Ø 4 mm | — |
| | Female/Female/Female (FFF) | — | — | Ø 6 mm |
| Operating pressure | bar | 2 → 8 | 2 → 8 | 2 → 8 |
| Vacuum pad material | | — | — | — |
| Weight | g | 80 | 13 | 25 |


Detection of the pressure decrease can be achieved by the use of manostats (see pages 38/39)




Dimensions

81 535 301


Sub-base mounting 81 531... and 81 532...



81 545 001




81 545 005



ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Pneumatic logic components



General characteristics

Operating fluid

- Compressed air or inert gas.

Conditions of use

- Operating pressure 2 at 8 bars (except for special conditions).
- Fluid: Filtered air to 50 microns - non lubricated.
- Operating temperature from - 5° C to + 50° C (under + 5° C the dew point must be below 10° C for the application).
- For optimum performance, the elements should be inter-connected by air supply tubing with an internal diameter \geq at 2.5 mm.


Mounting recommendations

- The elements should be mounted and piped in a clean atmosphere in order to prevent any form of pollution entering the system.
- Minimum torque for element fixing screws: 5 cm/kg.
- maximum torque for element fixing screws: 10 cm/kg.

Characteristics common to all elements in the modular system

- The characteristics have been obtained with a supply pressure at 6 bars.
- The flow in NL/min is the number of litres of air at normal atmospheric pressure obtained with the output open to atmosphere and the supply pressure at 4 bars
- The consumption in NL/min is the number of litres of free air necessary for the unit to function.
- KV = the flow coefficient of the equipment.
- Mechanical life > 10^7 operations.


flow graphs



Sequencer modules

Operation results from the combination of a sequential cycle. A system comprises individual modules which are joined together by means of a sub-base. Each module has a memory which delivers an output signal and receives an input signal.

An indicator on each module allows the operator to monitor the progress of the cycle and identify quickly and easily any fault which may occur.




Operation results from the combination of three functions (memory, AND and OR) which constitute each module.

The memory activates the output and gives priority to the reset signal. The AND element ensures the transition to the next module but only if an input signal is present.

The OR element ensures the resetting of all previously operated modules

Function diagram




sequencer module with maintained reset

Brake

This maintains the memory spool in position only when the supply is lost.

Module with auto reset



Brake


This returns the memory spool to the reset condition only when the supply is lost

Shift register


The general principle is to advance the sequencer step by command impulses to the inputs of the even steps, alternating with the command impulses to the inputs of the odd steps.

Used for example on a transfer machine to shift the information "bad component" collected at a test-test "n" steps further along the machine to a reject station.

Function diagram



Auto reset sequencer module



Sequencer modules

- 100 % pneumatic
- Ideal for a simple pneumatic sequence

 Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive

Versions sequencer
shift register

81 550 001

with 'maintain'

81 550 201



Reset to zero

81 550 401

—

81 550 601


Reset to zero



Symbol

Characteristics


| | | | | | |
|---|--------|----------|----------|----------|----------|
| Operating pressure | bar | 2 → 8 | 2 → 8 | 2 → 8 | 2 → 8 |
| Orifice diameter | mm | 2.7 | 2.7 | 2.7 | 2.7 |
| Flow at 6 bars | Nl/min | 150 | 150 | 150 | 150 |
| Operating temperature | °C | -5 → +50 | -5 → +50 | -5 → +50 | -5 → +50 |
| Mechanical life 5 x 10 ⁶ at 6 bars | | ● | ● | ● | ● |
| Connection - Sub-base page 26 | | ● | ● | ● | ● |
| Weight | g | 70 | 70 | 70 | 70 |



Principle of operation


(supplied without logic element. For choice of units see pages 46/47)

Sequencer module with maintained reset




- 1 - Input signal
- 2 - Supply
- 3 - Output signal
- 4 - Start signal
- 5 - In cycle signal
- 6 - End of cycle signal
- 7 - Reset to zero signal

Shift register with maintained reset




- 1 - Input signal
- 2 - Supply
- 3 - Output signal
- 4 - Start signal
- 5 - In cycle signal
- 6 - End of cycle signal
- 7 - Reset to zero signal

Dimensions



Mounting plan for sequencer




ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Sequencer sub-bases



Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



| | | | |
|----------|------------------------------|------------|----------------------|
| Versions | Front connecting (DIN-omega) | 81 551 101 | Sub-base (DIN oméga) |
| | Rear connecting (with clips) | — | 81 552 101 |

| | |
|------------|----------------------|
| 81 552 101 | End bases - one pair |
| — | 81 552 601 |

| | |
|------------|----------------|
| 81 552 601 | Diversion base |
| — | — |

Characteristics




| | | |
|-----------------------|-------------------------------|----------|
| Sub-bases | Rotatable connectors (fitted) | • |
| Pressure indicators | • | • |
| Operating temperature | °C | -5 → +50 |
| Weight | g | 55 |

| | | |
|-----------------------|-------------------------------|----------|
| Sub-bases | Rotatable connectors (fitted) | • |
| Pressure indicators | • | • |
| Operating temperature | °C | -5 → +50 |
| Weight | g | 135 |

| | | |
|-----------------------|-------------------------------|----------|
| Sub-bases | Rotatable connectors (fitted) | • |
| Pressure indicators | • | • |
| Operating temperature | °C | -5 → +50 |
| Weight | g | 60 |

Sequencer connections


Front connecting




- 1 - Input port (green port 1) Ø 4
- 2 - Output port (red port 1) Ø 4
- 3 - Input port, cycle start (green port 1) Ø 4
- 4 - Output port, in-cycle signal (red port 1) Ø 4
- 5 - Output port, cycle end (red port 6) Ø 4
- 6 - Output port, cycle end (red port 6) Ø 4
- 7 - Input port, reset to zero (green port 7) Ø 4
- 8 - Output indicator (red)
- 9 - Input indicator (green)
- 10 - Cycle start indicator at port 4 (green)
- 11 - In-cycle indicator at port 5 (red)
- 12 - Input indicator at port 7 (green)
- 13 - End of cycle indicator at port 6 (red)
- 14 - Supply indicator at port 2 (yellow)
- 15 - Interconnecting ports
- 16 - Fixing screws
- 17 - Engraved arrow to indicate direction of sequence
- 18 - Marking tag
- 19 - Marking tag position
- 20 - Marking tag position
- 21 - Mounting tongue
- 22 - Mounting groove
- 23 - Sub-base
- 24 - End bases

Dimensions

Front connecting








81 551 001





Sub-base (with clips)

81 552 001

End bases - one pair

 $-5 \rightarrow +50$
40 $-5 \rightarrow +50$
120**Rear connecting**

- 1 - Input port (marked port 1)
- 2 - Supply port (Port 2)
- 3 - Output port (Port 3)
- 4 - Cycle start signal port (Port 4)
- 5 - In-cycle signal port (Port 5)
- 6 - End of cycle signal port (Port 6)
- 7 - Reset to zero signal port (Port 7)
- 8 - Indicator at supply port
- 9 - Marking area


**Rear connecting**

ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Logic elements



- Performs "combined" Pneumatic
- Easy to use

Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



| | | | | | |
|-----------|------------------------|-------------------------------|----------------|----------------|-------------------------------|
| Functions | OR AND YES NO | 81 521 501 | 81 540 001 | 81 540 005 | 81 522 501 |
| Version | | On Sub-base page 4/14-4/15 | Plug-in Ø 4 | Plug-in Ø 6 | On Sub-base page 4/14-4/15 |

Symbol




Characteristics

| | | | | | |
|--|----------------------|------------------|------------------|------------------|------------------|
| Push-in connection for semi-rigid tubing (NFE 49100) | Male/Female/Female | — | Ø 4 mm | — | — |
| Colour | Female/Female/Female | — | — | — | — |
| Operating pressure | bar | 2 → 8 | Blue | Blue | Blue |
| Orifice diameter | mm | 2.7 | 2.7 | 2.7 | 2.7 |
| Flow at 6 bars | Nl/min | 170 | 170 | 200 | 170 |
| Pressure indicator | | ● | — | — | ● |
| Switching time | ms | — | — | — | — |
| Operating temperature | °C | -5 → +50 | -5 → +50 | -5 → +50 | -5 → +50 |
| Mechanical life | operations | >10 ⁷ | >10 ⁷ | >10 ⁷ | >10 ⁷ |
| Weight | g | 25 | 12 | 25 | 25 |

Pilot/pressure curves

P_p : Pilot pressure
P_a : Supply pressure

Principle of operation




Cellule OR

The output signal "S" is present when a signal at "a" OR "b" is present:

$$S = a \text{ OR } b$$

$$S = a + b$$



Cellule AND


The output signal "S" is present only when signals "a" AND "b" are present simultaneously:

$$S = a \text{ AND } b$$


$$S = a \cdot b$$

Dimensions


81 521 501 - 81 522 501



81 540 005 - 81 541 005




81 540 001 - 81 541 001



Other information

See pages 54/55 for mounting plan for logic elements.



81 541 001

Plug-in
Ø 4

81 541 005

Plug-in
Ø 6

81 501 025

On sub-base
page 36-37

81 503 025






Threshold
On sub-base page
4/14-4/15

81 504 025

Threshold
On sub-base page
4/14-4/15

81 506 025

Threshold
On sub-base page
4/14-4/15



Ø 4 mm

—

Green

$2 \rightarrow 8$

2.7

150

—

—

$-5 \rightarrow +50$

$>10^7$

13

—

Ø 6 mm

—

Green

$2 \rightarrow 8$

4

200

—

—

$-5 \rightarrow +50$

$>10^7$

25

—

Yellow

$2 \rightarrow 8$

2.7

170

—

—

< 4

$-5 \rightarrow +50$

$>10^7$

30

—

Orange

$2 \rightarrow 8$

2.7

170

—

—

< 4

$-5 \rightarrow +50$

$>10^7$

30

—

Light grey

$2 \rightarrow 8$

2.7

170

—

—

< 4

$-5 \rightarrow +50$

$>10^7$

30

—

Dark grey

$2 \rightarrow 8$

2.7

170

—






—

< 4

$-5 \rightarrow +50$

$>10^7$

30




YES element

The output signal "S" is only present when the pilot is present "a" is present:

$$S = a \text{ YES } b$$

$$S = a$$



NOT element

The output signal "S" is present only if the input signal "a" is NOT present. The output signal is therefore the inverse of the pilot signal:


$$S = \text{NOT } a$$

If the supply port is connected to a 2nd input "b", the function obtained is called inhibition:

$$S = \text{NOT } a \text{ AND } b$$

$$S = \bar{a}$$

81 501 025 - 81 503 025
81 504 025 - 81 506 025



ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Memory element

- 100 % pneumatic
- Bistable pneumatic



Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Version


81 523 201

With pressure indicator

81 523 601

With pressure indicator and manual override

Symbol




Characteristics

| | | |
|---|----------------|----------------|
| Colour | Black | Black |
| Operating pressure | bar 2 → 8 | bar 2 → 8 |
| Orifice diameter | mm 2.7 | mm 2.7 |
| Minimum memory pilot pressure | bar 2.5 | bar 2.5 |
| Operating temperature | °C -5 → +50 | °C -5 → +50 |
| Flow at 6 bars | NI/min 200 | NI/min 200 |
| Connection - On sub-base page 4/14-4/15 | • | • |
| Weight | g 90 | g 90 |

Principle of operation


The function is that of a 4/2 valves. The appearance of signal "X1" causes the displacement of the slide valve. The output port "x" is then put under pressure. This state is remembered until the arrival of signal "X0". This signal reverses the slide valve, the output "x" is put under pressure. This state is likewise remembered. The output:

- "x" under pressure indicates that the information in the MEMORY is "X1",
- "x" under pressure indicates that the information in the MEMORY is "X0".




Dimensions

81 523 201 - 81 523 601



Dimensions of logic and memory elements



Viewed from above

ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Timers fixed timing

■ Fixed 0.4 s




Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Version

81 503 540
Positive output


Symbol




Characteristics

| | | |
|-------------------------------------|------------|------------------|
| Timing | s | 0.4 |
| Operating pressure | bar | 2 → 8 |
| Flow at 6 bars | Nl/min | 170 |
| Orifice diameter | mm | 2.7 |
| Accuracy | % | ± 5 |
| Min. reset time | s | <0.1 |
| Connection - On sub-base page 36-37 | | ● |
| Operating temperature | °C | -5 → +50 |
| Mechanical life | operations | >10 ⁷ |
| Weight | g | 106 |

Principle of operation with positive output



Dimensions 81 503 540



ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Timers (with adjustable timing)


■ 60 s adjustable (60 s max.)

Also available in ATEX version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



| | 81 503 710 | 81 506 710 | 81 503 720 | 81 506 720 | 81 503 725 | 81 506 725 |
|----------|----------------------|------------|------------|------------|------------|------------|
| Function | positive negative | ● | — | ● | — | ● |
| | | | | | | |

Symbol



Characteristics

| | | | | | | | |
|---|------------|------------------|------------------|------------------|------------------|------------------|------------------|
| Timing | s | 0.1 → 15 | 0.1 → 15 | 0.1 → 30 | 0.1 → 30 | 0.1 → 60 | 0.1 → 60 |
| Operating pressure | bar | 2 → 8 | 2 → 8 | 2 → 8 | 2 → 8 | 2 → 8 | 2 → 8 |
| Flow at 6 bars | Nl/min | 170 | 170 | 170 | 170 | 170 | 170 |
| Orifice diameter | mm | 2.7 | 2.7 | 2.7 | 2.7 | 2.7 | 2.7 |
| Accuracy | % | ± 5 | ± 5 | ± 5 | ± 5 | ± 5 | ± 5 |
| Min. reset time | s | <0.1 | <0.1 | <0.1 | <0.1 | <0.1 | <0.1 |
| Connection - On sub-base page 4/14-4/15 | | ● | ● | ● | ● | ● | ● |
| Operating temperature | °C | -5 → +50 | -5 → +50 | -5 → +50 | -5 → +50 | -5 → +50 | -5 → +50 |
| Mechanical life | operations | >10 ⁷ |
| Weight | g | 90 | 90 | 100 | 100 | 120 | 120 |

Accessories

| | | | | | | |
|------------------------|------------|------------|------------|------------|----|---|
| Panel mounting adaptor | 79 451 698 | 79 451 698 | 79 451 903 | 79 451 903 | — | — |
| Weight | g | 53 | 53 | 53 | 53 | — |

Principle


The operation of these pneumatic timers is similar to that of electronic timers (circuit with capacitor/resistor)

Principle of operation

with positive output



with negative output

Timing by charging of reservoir




The reservoir fills via the flow restrictor until the switching point of the timer output is reached (positive or negative).

The non-return valve allows the reservoir to be emptied rapidly for the next timing.




Dimensions



| | L (mm) |
|-------------------------|--------|
| 81 503 710 - 81 506 710 | 78 |
| 81 503 720 - 81 506 720 | 92 |
| 81 503 725 - 81 506 725 | 125 |

Adaptor 79 451 ...



For panel mounting, a pre-drilled hole Ø 10.5 mm is required

ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Timers



■ Fixed and adjustable

Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive

Single impulse generator

Fixed
Adjustable



81 507 540


Adjustable frequency generator

—
—

81 507 720
—
—

—
—
81 506 940

Symbol



Characteristics



| | | | | |
|---|------------|------------------|------------------|------------------|
| Timing | s | 0.4 | 0.1 → 30 | — |
| Frequency | Hz | — | — | 0.02 → 8 |
| Operating pressure | bar | 2 → 8 | 2 → 8 | 2 → 8 |
| Flow at 6 bars | Nl/min | 170 | 170 | 170 |
| Orifice diameter | mm | 2.7 | 2.7 | 2.7 |
| Accuracy | % | ± 5 | ± 5 | ± 5 |
| Min. reset time | s | <0.1 | <0.1 | <0.1 |
| Connection - On sub-base page 4/14-4/15 | | • | • | • |
| Operating temperature | °C | -5 → +50 | -5 → +50 | -5 → +50 |
| Mechanical life | operations | >10 ⁷ | >10 ⁷ | >10 ⁷ |
| Weight | g | 106 | 180 | 85 |

Accessories



| | | | |
|-------------------------|---|------------|------------|
| Panel mounting adaptors | — | 79 451 904 | 79 451 905 |
| Weight (g) | — | 53 | 53 |

Principle of operation



Single impulse generator






Adjustable impulse generator




Frequency generator



Dimensions




| Part numbers | L (mm) |
|--------------|--------|
| 81 507 540 | 73 |
| 81 507 720 | 99 |
| 81 506 940 | 72 |



For panel mounting, a pre-drilled hole Ø 10.5 mm si required

ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com


Timing Accessories



 Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive

| One-way in-line fixed flow restrictors | Flow at 4 bars Nm ³ /h | Ø orifice (mm) | | — | — | — |
|--|--------------------------------------|----------------|------------|------------|------------|------------|
| | | 0.18 → 0.30 | 0.3 → 0.50 | | | |
| | 0.35 → 0.50 | 0.4 | yellow | 81 529 004 | — | — |
| | 0.58 → 0.77 | 0.5 | red | 81 529 005 | — | — |
| | 0.80 → 1.06 | 0.6 | green | 81 529 006 | — | — |
| | 1.10 → 1.39 | 0.7 | blue | 81 529 007 | — | — |
| | 1.45 → 1.65 | 0.8 | grey | 81 529 008 | — | — |
| | 2.30 → 2.80 | 1 | black | 81 529 010 | — | — |
| | 0.08 → 0.12 | 0.25 | white | 81 529 025 | — | — |
| One-way adjustable flow restrictor | — | — | — | 81 525 101 | 81 526 001 | — |
| Capacity for timing | 10 • 60 s | — | — | — | — | 79 458 808 |

Symbol



Characteristics


| | | | | | |
|-----------------------|---|----------------------|----------|----------|----------|
| Free flow | NI/min | Depending on orifice | 30 | 200 | — |
| Orifice diameter | mm | Depending on orifice | 0 → 0.5 | 0 → 1.7 | — |
| Operating pressure | bars | 1 → 8 | 1 → 8 | 2 → 8 | — |
| Timing | s | — | — | — | 10 → 60 |
| Capacity | cm ³ | — | — | — | 30 |
| Connection | Sub-base page 4/14-4/15 Push-in connection for semi-rigid tubing (NFE 49100) | mm | Ø 4 | ● | ● |
| Operating temperature | °C | -5 → +50 | -5 → +50 | -5 → +50 | -5 → +50 |
| Weight | g | 8 | 60 | 70 | 40 |

Connections

For timing circuit


- One-way flow restrictor 81 525 1 - 81 529 0 (1)
- Reservoir 79 458 018 (2)
- Relay element 81 503 0 - 81 506 0 (3) page 4/6-4/7

Sub-base page 4/14-4/15




Principle of operation

One-way with fixed flow



One-way
with adjustable flow




Dimensions

81 529

81 525 101

81 526 001

79 452 808



ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Regulator accessories



Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Part numbers

Mini-détenteur

81 527 001

— — —


Plug element

81 520 601

In-line non-return

81 529 901

Symbol




Characteristics


| | | | | |
|----------------------------|--|---------|-----|-------|
| Operating pressure | bars | 2 → 8 | — | 2 → 8 |
| Flow at 6 bars | Nl/min | 200 | — | 200 |
| Adjustable output pressure | bar | 0,1 → 8 | — | — |
| Connection | Sub-base | ● | ● | — |
| | Push-in connection for semi-rigid tubing (NFE 49100) | mm | Ø 4 | — |
| Weight | g | 150 | 70 | 70 |

Dimensions

81 529 901



81 520 601





ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Sub-bases for logic elements



Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



| | |
|--------------------------------------|----------|
| Two-hand start module | ● 1 |
| Manostats - vacuostats | ● 1 |
| Leak sensor and amplifier relays | ● 1 |
| Logic elements AND Timers | ● 1 |
| Regulator accessories | ● 1 |
| Memory element | — |
| Operating temperature °C | -5 → +50 |
| Electro-pneumatic miniature solenoid | ● 1 |

| | |
|------------|-----|
| 81 532 104 | ● 1 |
| 81 532 102 | ● 1 |
| | ● 1 |
| | ● 1 |
| | ● 1 |
| | ● 1 |
| | — |
| | — |
| | ● 1 |

| | |
|------------|-----|
| 81 532 102 | ● 1 |
| | ● 1 |
| | ● 1 |
| | ● 1 |
| | ● 1 |
| | — |
| | — |
| | ● 1 |


NB: The number indicates the number of components mounted on the sub-base

Characteristics

| | | |
|--|----------------|----------------|
| Push-in connection for semi-rigid tubing Ø 4 mm (NFE 49100) | rotatable | rotatable |
| Fixation | DIN rail 35 mm | DIN rail 35 mm |
| Weight | g 56 | g 52 |

Connections elements and relays

Front connecting




- A - Single sub-base or end base
- B - Associateable sub-base
- 1 - Input port (green port 1)
- 2 - Output port (red port 3)
- 3 - Input/supply port (yellow port 2) Ø 4
- 4 - Input port integral to sub-base
- 5 - Input indicator (green)
- 6 - Output indicator (red)
- 7 - 1/4 turn screws
- 8 - Marking tag
- 9 - Arrow indicating flow direction
- 10 - Mounting tongue
- 11 - Mounting groove
- 12 - Selector


Dimensions

81 532 104

3 x 81532102



ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com




| | | | |
|--------------------------------------|------------|------------|------------|
| Two-hand start module | 81 542 002 | 81 532 001 | 81 531 001 |
| Manostats - vacuostats | — | ● 1 | ● 2 |
| Leak sensor and amplifier relays | — | ● 1 | ● 2 |
| Logic elements AND Timers | — | ● 1 | ● 2 |
| Regulator accessories | — | ● 1 | ● 2 |
| Memory element | ● 1 | — | ● 1 |
| Operating temperature °C | -5 → +50 | -5 → +50 | -5 → +50 |
| Electro-pneumatic miniature solenoid | — | ● 1 | ● 2 |


Caractéristiques

| | | | |
|---|----------------|-------------|------------------------|
| Push-in connection for semi-rigid tubing Ø 4 mm (NFE 49100) | rotatable | rear | rear |
| Fixation | DIN rail 35 mm | 2 M4 screws | Clips for rails Ø 8 mm |
| Weight g | 95 | 10 | 35 |

Memory element sub-base, front and rear connecting



Rear connection



The modular system elements are fixed with two screws on the sub-base.

A locating device on each logic element prevents incorrect assembly.




The logic element is connected via the sub-base. This sub-base has 3 instant connections for connecting semi-rigid tubes with outer Ø 4.

- 1 - Input signal
- 2 - Signal port for passive logic elements, air supply for active logic elements.
- 3 - Output signal

81 542 002 (for memory 81523201/601)

81 531 001


81 532 001



ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Mounting accessories

 Also available in **ATEX** version
for use in potentially explosive
atmospheres in accordance
with 94/9/EC Directive




| | | | | | |
|----------------------------|---------------------------|---------------------------|--------------------------------|------------|---|
| Mounting equipment | 81 533 501 Hole domino | 81 533 001 Clip domino | 79 450 609 Bar clips Ø 8 | | — |
| Supply manifold 13 outputs | — | — | — | 81 536 801 | — |

Characteristics

| | | | | |
|--------------------------|--|--|-------------------------|----------|
| Weight (g) | 8 | 4 | 80 | 80 |
| | For mounting on the end of a zinc-coated mild steel rod Ø 8 mm on an asymmetrical DIN rail | For adjustable mounting on a zinc-coated mild steel rod Ø 8 mm on an asymmetrical DIN rail | Packet of 100 pieces | |
| Operating temperature °C | -5 → +50 | -5 → +50 | -5 → +50 | -5 → +50 |

Dimensions

81 536 804



Other information

Use Weidmuller plastic labels for marking components part number FW 4734-6.

ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Electro-pneumatic control valves



Miniature solenoid valves for alternating current

| |
|---|
| ■ Conform to the Low Voltage Directive |
| ■ For mounting on sub-base or footprint in accordance with CNOMO recommendation E-06-36-120N |



Part numbers (and voltages)

| Consumption | Voltage | 81 519 080 | 81 519 380 | 81 519 680 |
|-------------|-------------------------|------------|------------|------------|
| 2.5 VA | 24 V ~ 50-60 Hz | — | — | — |
| 2.5 VA | 48 V ~ 50-60 Hz* | — | 81 519 381 | — |
| 2.5 VA | 110 V ~ 50-60 Hz | — | 81 519 378 | 81 519 678 |
| 2.5 VA | 220 V- 230 V ~ 50-60 Hz | — | 81 519 379 | 81 519 679 |

Function
Version


| | | |
|-------------------------|---------------------------------|---|
| 3/2 NC | 3/2 NC | 3/2 NC |
| Without manual override | With manual override by impulse | With manual override by latching (1/4 turn) |

Characteristics

| | | | | |
|---|---------|-------------------|-------------------|-------------------|
| Operating pressure | bar | 1 → 8 | 1 → 8 | 1 → 8 |
| Orifice diameter | mm | 0.5 | 0.5 | 0.5 |
| Flow at 6 bars | Nl/min | 12 | 12 | 12 |
| kV | | 0.12 | 0.12 | 0.12 |
| Switching time | ms | 5 → 15 | 5 → 15 | 5 → 15 |
| Mechanical life (operations) | | 5 10 ⁷ | 5 10 ⁷ | 5 10 ⁷ |
| Operating temperature | °C | -10 → +50 | -10 → +50 | -10 → +50 |
| Compressed air or inert gas - oil-free air filtered to 50 µ | | • | • | • |
| Duty factor | | 100 % ED | 100 % ED | 100 % ED |
| Insulation class | IEC 85 | F | F | F |
| Weight | | 35 | 35 | 35 |
| Rotatable connector 4 positions in 90° steps | | • | • | • |
| Degree of protection with sub-base (page 62) | IEC 529 | IP 20 | IP 20 | IP 20 |
| protection with connector 81 516 082 (page 65) | IEC 529 | IP 65 | IP 65 | IP 65 |
| UL and cUL approval | | MH 15085 | MH 15085 | MH 15085 |


15x15 mm footprint

according to CNOMO E 06-36-120N



Dimensions 81 519 0

81 519 3
81 519 6



Miniature solenoid valves for direct current

- Conform to the Low Voltage Directive
- For mounting on sub-base or footprint in accordance with CNOMO recommendation E-06-36-120N



Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Part numbers (and voltages)


| | Consumption 1 W | Voltage 24 V | 81 519 032 | 81 519 332 | 81 519 632 | 81 519 340 |
|----------|--------------------|-----------------|-------------------------|---------------------------------|---------------------------------|---------------------------------|
| Function | | | 3/2 NC | 3/2 NC | 3/2 NC | 3/2 NF |
| Version | | | Without manual override | With manual override by impulse | With maintained manual override | With maintained manual override |

Characteristics

| | | | | | |
|---|---------|-------------------|-------------------|-------------------|-------------------|
| Operating pressure | bar | 1 → 8 | 1 → 8 | 1 → 8 | 1 → 8 |
| Orifice diameter | mm | 0.8 | 0.8 | 0.8 | 0.8 |
| Flow at 6 bars | Nl/min | 25 | 25 | 25 | 25 |
| kV | | 0.3 | 0.3 | 0.3 | 0.3 |
| Switching time | ms | 5 → 15 | 5 → 15 | 5 → 15 | 5 → 15 |
| Mechanical life (operations) | | 5 10 ⁷ | 5 10 ⁷ | 5 10 ⁷ | 5 10 ⁷ |
| Operating temperature | °C | -10 → +50 | -10 → +50 | -10 → +50 | -10 → +50 |
| Compressed air or inert gas - oil-free air filtered to 50 µ | | • | • | • | • |
| Duty factor | | 100 % ED | 100 % ED | 100 % ED | 100 % ED |
| Insulation class | IEC 85 | F | F | F | F |
| Weight | | 35 | 35 | 35 | 35 |
| Rotatable connector 4 positions in 90° steps | | • | • | • | • |
| Degree of protection with M12 5-pin connector with connector 81 516 082 | IEC 529 | — | — | — | — |
| UL and cUL approval | | IP 65 MH 15085 | IP 65 MH 15085 | IP 65 MH 15085 | IP 65 MH 15085 |


15x15 mm footprint

according to CNOMO E 06-36-120N




Adjacent side of footprint when valves mounted in bank


Encombrement 81 519 0



**81 519 3
81 519 6**



81 519 3




ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Sub-bases for miniature solenoid valves



Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Part numbers


| | | | |
|---|-------------------|-------------------|-------------------|
| Pair of end bases | 81 514 101 | — | — |
| Intermediate sub-base | — | 81 514 161 | — |
| Adaptor sub-base for CNOMO 06-05-80 / NFE 49066 footprint | — | — | 79 453 569 |

Characteristics

| | | | |
|---|-------------------|----------------|------------------|
| Pneumatic indicator on output | • | • | • |
| Common supply | • | • | • |
| Common exhaust | • | • | • |
| Torque capacity | mm ² 3 | mm 3 | mm 3 |
| Push-in connection for semi-rigid tubing Ø 4 mm (NFE 49100) | • | • | • |
| Mounting | DIN rail 35 mm | DIN rail 35 mm | 2 screws M4 x 10 |
| UL and cUL approval | MH 15085 | MH 15085 | — |
| Weight | 9 | 65 | 30 |


Connection

Pneumatic



- 1 - Supply
- 2 - Output
- 3 - Exhaust


Electrical



- A1 - Pilot signal
- A2 - Common
- - Earth

Dimensions with miniature solenoid valve (page 58)

81 514 101 - 81 514 161



79 453 569


Connector ref 81 516 082
(rotatable in 90° steps)
see page 65

Miniature solenoid valve 81 519 ...
see page 58

CNOMO footprint
E 06-36-120N for mounting
miniature solenoid valve 81 519

Mounting on CNOMO 06-05-80/
NFE 49066 footprint


Fixing on CNOMO 06-05-80/
NFE 49-066 footprint by
2 cap screws M4x10
(NFE 25-127)



ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Electro-pneumatic miniature control valves

Mounting



Valve modules

- Monostable, bistable
- 3/2, 4/2



Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



81 513 100

81 513 600


81 513 200

81 516 200

81 516 100

| Function | 3/2 NC monostable | 3/2 NO monostable | 4/2 monostable | 4/2 bistable | 4/2 monostable |
|----------|-------------------|-------------------|----------------|--------------|----------------|
|----------|-------------------|-------------------|----------------|--------------|----------------|

Symbol




Characteristics


| | | | | | | |
|-----------------------------------|--------------------------------|-----------------------|-----------------------|-----------------------|-----------------|-----------------|
| Width | mm | 17.5 | 17.5 | 17.5 | 35 | 35 |
| Working pressure | bars | 3→8 | 3→8 | 3→8 | 2→8 | 3.5→8 |
| Orifice diameter | mm | 3 | 3 | 3 | 4 | 4 |
| Flow at 6 bars | with Ø 4 mm sub-base (page 63) | 200 | 200 | 200 | 300 | 300 |
| | with Ø 6 mm sub-base (page 63) | 300 | 300 | 300 | 400 | 400 |
| Flow Rate | with Ø 4 mm sub-base (page 63) | 2.2 | 2.2 | 2.2 | 4 | 4 |
| | with Ø 6 mm sub-base (page 63) | 2.5 | 2.5 | 4 | 5 | 5 |
| Operating temperature | ° C | -10 → +50 | -10 → +50 | -10 → +50 | -10 → +50 | -10 → +50 |
| Switching time for the valve only | ms | 15 | 15 | 15 | 50 | 50 |
| Mechanical life | operations | 1.5 x 10 ⁷ | 1.5 x 10 ⁷ | 1.5 x 10 ⁷ | 10 ⁷ | 10 ⁷ |
| Weight | g | 38 | 38 | 38 | 106 | 106 |

Dimensions

81 513



81 516




ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Sub-bases and end bases for miniature control valves



Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Part numbers

| Mounting | Cabinet | Cabinet | Cabinet | Cabinet |
|--|---|--|------------------------------------|---|
| Version | 17.5 mm | 35 mm | — | — |
| Push-in connection for semi-rigid tubing (NFE 49100) | Sub-bases Ø 4 mm Ø 6 mm End bases (pair) Ø 6 mm Intermediate supply module Ø 6 mm | 81 513 060 81 513 065 81 513 201 — — | 81 517 101 81 517 201 — — | — — 81 513 011 — 81 513 001 |


Characteristics

| | | | | | |
|---------------------|-----------------|----------------|----------------|----------------|----------------|
| Torque capacity | mm ² | 3 | 3 | — | — |
| UL and cUL approval | | MM15085 | MM15085 | — | — |
| Mounting | | DIN rail 35 mm |
| Weight | g | 55 | 110 | 86 | 44 |

Connections Pneumatic




2 - Pneumatic output 4/2 (NO)
4 - Pneumatic output 3/2 or 4/2 (NC)



② Output at rest (NO)
② Output at rest *
④ Output at rest *
4 Output operating (NC)

81 513 011 - 81 513 001



Note :


- Each sub-base can accept
- sub-base 81 513 060-065 : 1 relay 3/2 or 4/2, width 17.5 mm
- sub-base 81 517 101-201 : 1 bistable relay 4/2 (width 35 mm) or 2 relays 3/2 or 4/2 (width 17.5 mm)

② 2 Supply ports

③ 2 Exhaust ports

Integral push-in connections Ø 6 mm


Electrical



A1 - Pilot signal

A2 - Common

— Earth



A1 - Operating control signal (14)

A2 - Common


A1 - Rest control signal (12)

A2 - Common

— Earth


Degree of protection :
IP20 when assembled.

Dimensions with miniature control valves (page 62) + miniature solenoid valves (page 58) + indicators (page 65)



ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Valves and solenoids valves assembled



Contact us for
Other versions

Part numbers

| | | |
|--|--|--|
| Function | 3/2 NC | 4/2 monostable |
| Sub-base with push-in connection for semi-rigid tubing (NFE 49100) | Ø 4 ext. | Ø 4 ext. |
| Version | Solenoid valve with manual override by impulse | Solenoid valve with manual override by impulse |
| Voltage | 24 VDC (+10% -15%) | 81 513 103 81 513 203 |


Symbol




Characteristics

| | | | |
|--|----------------|-----------------------|-----------------------|
| Operating pressure | bar | 3 → 8 | 3 → 8 |
| Orifice diameter | mm | 3 | 3 |
| Flow at 6 bars | NL/min | 200 | 200 |
| with sub-base 81 513 060 | NL/min | — | — |
| KV with sub-base 81 517 101 | | 2.2 | 2.2 |
| Operating temperature | °C | -10 → +50 | -10 → +50 |
| Switching time of the assembly | ms | 20 | 20 |
| Mechanical life (operations) at 4 bars | | 1.5 x 10 ⁷ | 1.5 x 10 ⁷ |
| Valve position will be maintained in the event of pressure loss and/or electrical current loss | | — | — |
| Mounting | DIN rail 35 mm | DIN rail 35 mm | |
| Weight | g | 130 | 130 |
| UL and cUL approval | | MH15085 | MH15085 |


Principle of operation




4/2 monostable module



4/2 bistable module



Dimensions



End bases not supplied (page 63)
Intermediate bases not supplied (page 63)
Indicators not supplied (page 65)

Accessories




Also available in **ATEX** version for use in potentially explosive atmospheres in accordance with 94/9/EC Directive



Part numbers

| | | | | | | | |
|---|---------------------------------|------------|---|------------|------------|---|------------|
| Visual indicators with anti-surge | 24 V - 50-60 Hz | 81 513 052 | — | — | — | — | — |
| | 48 V - 50-60 Hz | 81 513 055 | — | — | — | — | — |
| | 110 V - 50-60 Hz | 81 513 058 | — | — | — | — | — |
| | 230 V - 50-60 Hz (-10% +6 %) | 81 513 059 | — | — | — | — | — |
| LED seal Packaging | 12 to 24 V - DC - AC (by 5) | 81 513 064 | — | — | — | — | — |
| Exhaust silencer | Plug-in Ø 6 | — | — | 81 537 001 | — | — | — |
| | Plug-in Ø 8 | — | — | 81 537 201 | — | — | — |
| Connector for solenoid valve | — | — | — | 81 516 082 | — | — | — |
| Pneumatic pilots | Without manual override | — | — | — | 81 516 081 | — | — |
| | With manual override by impulse | — | — | — | 81 516 091 | — | — |
| Push-in connection for semi-rigid tubing Ø 4 mm (NFE 49100) | — | — | — | — | ● | — | — |
| Blanking plate | — | — | — | — | — | — | 81 516 085 |


Symbol



Characteristics

| | | | | | | | |
|---|----|---|------------|----|----|---------------------|---|
| Consumption | W | — | 0.24 | — | — | — | — |
| Temperature | °C | — | - 10 → +50 | — | — | — | — |
| Connection | mm | — | — | — | — | Instantané Ø 4 ext. | — |
| Mounted between the pilot solenoid valve and the body of the module | ● | ● | — | — | — | — | — |
| Supplied in multiples of 5 | ● | — | — | — | — | — | — |
| Supplied in multiples of 10 | — | ● | — | — | ● | ● | ● |
| Packet of 10 pieces | — | — | — | — | — | — | ● |
| Weight | g | 6 | 2 | 30 | 10 | 5 | 3 |


Connection



Dimensions


81 537 001 - 81 537 201

Mounted by plugging into push-in connector for semi-rigid tubing (NFE 49100)




81 513 052 - 81 513 055

81 513 058 - 81 513 059



81 516 082



ATEX version products are available in the following catalogues: **Pneumatic products for explosive atmospheres** or on our website www.crouzet.com

Solenoid valves


- Reduced "dimensions"
- Mounted on sub-base



Part numbers and voltages

| | |
|-----------------|------------------------------------|
| Function | 3/2 NC |
| Mounting | On sub-base (54) |
| Solenoid valves | 81 519 732 |
| with | 24 V (+10% -15%) |
| manual | 24 V - 50/60 Hz (+10% -15%) |
| override | 48V - 50/60 Hz (+10% -15%) |
| by impulse | 110 V - 50/60 Hz (+10% -15%) |
| | 220 - 230 V - 50/60 Hz (+10% -15%) |
| | 81 519 774 |
| | 81 519 775 |
| | 81 519 776 |
| | 81 519 777 |


Symbol



Characteristics

| | | |
|---|------------|-----------------------|
| Operating pressure | bar | 2 → 8 |
| Orifice diameter | mm | 2.7 |
| Flow at 6 bars | l/min | 170 |
| Rotatable coil 4 positions in 90° steps | | • |
| Degree of protection (with connector 81 516 082 not supplied) (see page 65) | IEC 529 | IP 65 |
| Mechanical life | operations | 1.5 x 10 ⁷ |
| Consumption | W | 1 |
| Operating temperature | VA | 2.5 |
| Weight | °C | -5 → +50 |
| UL and cUL approval | g | 70 |
| | | MH15085 |

Principle of operation





Connections

| | | |
|------------|---|----------------------|
| Pneumatic | { | 1 - Supply |
| | | 2 - Output |
| Electrical | { | 1 - 2 - Pilot signal |
| | | ↓ Earth |

Electrical connection by connector
81 516 062 (see page 65)


Dimensions 81 519

On separate sub-base



► Specific islands "for integrators" (supplied in packs of 20)

► Versions with interfaces 300 NL / mm



Configuration

- 1 - Specify the number and type of interfaces (3 / 2 mono - 4 / 2 mono - 4 / 2 bistable) see page 62.
- 2 - Specify the voltage, the type and method of the control valve connections, see page: 58-59 (Example: 24 V DC with manual switch maintained, exit leads).
- 3 - Please send us your application specifying your requirements and quantities per year, and we will respond as soon as possible.

► Versions with interfaces 30 NL / mm



Configuration

- 1 - Specify the voltage, the type and method of the control valve connections, see page: 58-59 (Example: 24 V DC with manual switch maintained, exit leads).
- 2 - Please send us your application specifying your requirements and quantities per year, and we will respond as soon as possible.


► Develop customised versions to specifications



Crouzet analyses your needs and offers a customised solution.



www.PCAEST.IT

Multi-fluid solenoid valves



Standard 2/2 miniature solenoid valves for fluids and inert gases

- Autonomous
- Mounted individually or in a battery
- Variable orientation coil
- Low power consumption : 1 W
- Quick to fit together, no tools needed
- M5 fittings or possibility of barb



Mounting

Individual

Bank end valves (1 pair)

Intermediate valve

Part numbers

| Orifice diameter | KV | Adjustment range | Power | NC | NC | NC |
|------------------|-----|------------------|-------|------------|----|------------|
| 0.8 mm | 0.3 | 1 • 8 b | 1W | 81 546 001 | | 81 547 501 |

Standard features

| | |
|--------------------------------------|--|
| Voltage | 24V --- |
| Electrical connections | 2.8 x 0.5 blade terminals (W7D5) at 9.4 mm centres |
| Fluid connection | tapped holes M5 |
| Manual override + pressure indicator | without |

General characteristics

| | |
|------------------------------|--------------------------------|
| Response time | 5 → 15 ms |
| Operating temperature | - 5 °C → +50 °C |
| Viscosity range | up to 30 cst |
| Vibration resistance | up to 5 g |
| Air flow rate (at 2 bars) | 15 → 40 Nl/mn |
| Maximum switching rate | 30 Hz |
| Weight Individual mounting | 32.5 g |
| Weight Bank end/inner valves | 35 g |
| Body material | Glass-reinforced polyamide 6.6 |
| Mechanical life (operations) | 1.5 x 10 ⁷ |
| UL and cUL approval | MH 15085 |


Accessories for 2/2 miniature solenoid valves

| | | |
|--|--|--|
| Connector for solenoid valve (see page 65) | 81 516 082 | |
| Visual indicators (see page 65) | 24 V-50/60 Hz CC 48 V-50/60 Hz AC 110 V-50/60 Hz AC 220 V-50/60 Hz AC | 81 513 052 81 513 055 81 513 058 81 513 059 |
| LED seal (see page 65) | 12-24 V ~ --- | 81 513 064 |

Dimensions


Individual

81 546 0




Bank end valves (1 pair)

81 547 0



Intermediate valve

81 547 5



Standard 3/2 miniature solenoid valves for fluids and inert gases

| |
|---|
| ■ Autonomous |
| ■ Mounted individually or in a battery |
| ■ All connections on one face |
| ■ Small size |



Mounting

Individual

Bank end valves (1 pair)

Intermediate valve

Part numbers

| Orifice diameter | KV Débit | Adjustment range | Power | NC | NC | NC |
|------------------|----------|------------------|-------|------------|------------|------------|
| 0.8 mm | 0.3 25 | 1 • 8 b | 1W | 81 548 010 | 81 549 010 | 81 549 510 |
| 0.8 mm | 0.3 | 1 • 8 b | 2W | | | |
| 1.2 mm | 0.6 40 | - 0.9 • 3 b | 2W | 81 548 011 | 81 549 011 | 81 549 511 |
| 1.5 mm | 0.8 60 | 0 • 2 b | 2W | 81 548 012 | 81 549 012 | 81 549 512 |

Standard features

| | |
|------------------------|--|
| Voltage | 24V --- |
| Electrical connections | 2.8 x 0.5 blade terminals (W7D5) at 9.4 mm centres |
| Fluid connection | tapped holes M5 |
| Manual override | by impulse |
| Pressure indicator | without |

General characteristics

| | |
|------------------------------|--|
| Response time | 5 → 15 ms |
| Operating temperature | - 5 °C → +50 °C |
| Viscosity range | up to 30 cst |
| Vibration resistance | up to 5 g |
| Air flow rate (at 2 bars) | 15 → 40 NL/min |
| Maximum switching rate | 30 Hz |
| Weight | Individual mounting Bank end/inner valves |
| Weight | 32.5 g 35 g |
| Body material | Glass-reinforced polyamide 6.6 |
| Mechanical life (operations) | 1.5 x 10 ⁷ |
| UL and cUL approval | MH 15055 |


Accessories for 3/2 miniature solenoid valves

| | | |
|--|--|--|
| Connector for solenoid valve (see page 5/11) | 81 516 082 | |
| Visual indicators (see page 65) | 24 V-50/60 Hz DC 48 V-50/60 Hz AC 110 V-50/60 Hz AC 220 V-50/60 Hz AC | 81 513 052 81 513 055 81 513 058 81 513 059 |
| LED seal (see page 65) | 12-24 V ~ --- | 81 513 064 |

Dimensions


Individual

81 548 0




Bank end valves (1 pair)

81 549 0



Intermediate valve

81 549 5



Teaching materials



Teaching materials

- Ideal for learning pneumatics
- For high schools, colleges and training centres



Part numbers


| | | |
|----------------------------|------------|------------|
| Training console PUMA 2000 | 81 598 940 | — |
| Add-on unit | — | 81 598 941 |
| Weight (kg) | 30 | 4 |

Characteristics

| | | |
|--|---|---|
| Maintained sequencer sub-base assembly | ● | — |
| 1 relay sub-base | ● | — |
| 1 peripheral sub-base | ● | — |
| 1 plate with 8 push-buttons | ● | — |
| 1 plate with 8 indicators | ● | — |
| 1 basic console | ● | — |
| 1 cylinder mounting plate (3 cylinders + control valves + position detectors) | ● | — |
| 2 electro-pneumatic interface units | — | ● |
| 1 pneumo-electrical interface unit | — | ● |

Dimensions

81 598 940



► List of part numbers

| Industrial part no. | ATEX part no. | Type | Pages | Industrial part no. | ATEX part no. | Type | Pages |
|---------------------|---------------|-------------------------|-------|---------------------|---------------|--------------------------|-------|
| 24 000 000 | | | | 81 507 540 | 81 507 543 | Frequency generator | 51 |
| 24 678 127 | | Pushbutton | 15 | 81 507 720 | 81 507 724 | Frequency generator | 51 |
| 24 678 128 | | Pushbutton | 15 | 81 508 110 | | Vacuum switch | 39 |
| 24 678 129 | | Pushbutton | 15 | 81 509 080 | | Pressure switch | 37 |
| 24 678 171 | | Mushroom button | 15 | 81 509 085 | | Pressure switch | 37 |
| 24 678 172 | | Mushroom button | 15 | 81 510 001 | | Amplifier relay | 34 |
| 24 678 173 | | Mushroom button | 15 | 81 512 201 | | Special detector | 31 |
| 24 678 174 | | Symmetrical toggle | 15 | 81 512 401 | | Special detector | 31 |
| 24 678 175 | | Lever toggle | 15 | 81 513 001 | 81 513 039 | Supply module | 63 |
| 24 678 176 | | Symmetrical toggle | 15 | 81 513 011 | 81 513 040 | End base | 63 |
| 24 678 177 | | Lever toggle | 15 | 81 513 052 | | LED | 65 |
| 24 678 178 | | Symmetrical toggle | 15 | 81 513 055 | | LED | 65 |
| 24 678 179 | | Lever toggle | 15 | 81 513 058 | | LED | 65 |
| 24 678 180 | | Key toggle | 15 | 81 513 059 | | LED | 65 |
| 24 678 181 | | Key toggle | 15 | 81 513 060 | 81 513 075 | Sub-base | 63 |
| 24 678 182 | | Key toggle | 15 | 81 513 064 | | Indicator seal | 65 |
| 24 679 702 | | Adaptor | 14 | 81 513 065 | 81 513 076 | Sub-base | 63 |
| 79 000 000 | | | | 81 513 100 | 81 513 196 | Valve module | 62 |
| 79 451 698 | 79 451 698 | Adaptor | 50 | 81 513 103 | | Valve module | 64 |
| 79 451 903 | 79 451 903 | Adaptor | 50 | 81 513 200 | 81 513 234 | Valve module | 62 |
| 79 451 904 | 79 451 904 | Adaptor | 51 | 81 513 203 | | Valve module | 64 |
| 79 451 905 | 79 451 905 | Adaptor | 51 | 81 513 501 | | Pressure switch | 36 |
| 79 452 103 | | Lever | 28 | 81 513 502 | | Pressure switch | 36 |
| 79 452 104 | | Lever | 28 | 81 513 509 | | Pressure switch | 37 |
| 79 452 123 | | Lever | 28 | 81 513 510 | | Pressure switch | 37 |
| 79 452 124 | | Lever | 28 | 81 513 516 | | Pressure switch | 37 |
| 79 452 133 | | Lever | 28 | 81 513 522 | | Vacuum switch | 36 |
| 79 452 808 | 79 458 018 | Capacity | 52 | 81 513 523 | | Vacuum switch | 37 |
| 79 453 569 | 79 453 569 | CNOMO sub-base | 60 | 81 513 527 | | Vacuum switch | 37 |
| 81 000 000 | | | | 81 513 533 | | Pressure switch | 37 |
| 81 280 010 | | NO Microvalve | 13-24 | 81 513 552 | | Pressure switch | 36 |
| 81 280 510 | | NF Microvalve | 13-24 | 81 513 600 | 81 513 612 | Valve module | 62 |
| 81 281 010 | | NO Microvalve | 13-24 | 81 514 101 | | Sub-base | 60 |
| 81 281 502 | | Limit switch | 25 | 81 514 161 | | Sub-base | 60 |
| 81 281 504 | | Limit switch | 25 | 81 516 081 | 81 516 093 | Pneumatic pilot | 65 |
| 81 281 508 | | Limit switch | 25 | 81 516 082 | | Connector | 65 |
| 81 281 509 | | Limit switch | 25 | 81 516 085 | 81 516 085 | Blanking plate | 65 |
| 81 281 510 | | NF Microvalve | 13-24 | 81 516 091 | | Accessories | 65 |
| 81 283 510 | | NF Microvalve | 24 | 81 516 100 | 81 516 107 | Valve module | 62 |
| 81 290 001 | 81 290 006 | Low-force detector | 23 | 81 516 200 | 81 516 208 | Valve module | 62 |
| 81 290 501 | 81 290 506 | Low-force detector | 23 | 81 517 101 | 81 517 106 | Sub-base | 63 |
| 81 371 401 | | Special detector | 32 | 81 517 201 | 81 517 206 | Sub-base | 63 |
| 81 372 201 | | Special detector | 32 | 81 519 032 | 81 519 035 | Miniature solenoid valve | 59 |
| 81 372 401 | | Special detector | 32 | 81 519 080 | | Miniature solenoid valve | 58 |
| 81 372 901 | | Special detector | 32 | 81 519 332 | 81 519 335 | Miniature solenoid valve | 59 |
| 81 501 025 | 81 501 031 | YES element | 47 | 81 519 340 | | Miniature solenoid valve | 59 |
| 81 502 110 | 81 502 111 | Vacuum switch | 39 | 81 519 378 | | Miniature solenoid valve | 58 |
| 81 502 140 | 81 502 141 | Pressure switch | 38 | 81 519 379 | | Miniature solenoid valve | 58 |
| 81 502 150 | 81 502 151 | Pressure switch | 38 | 81 519 380 | | Miniature solenoid valve | 58 |
| 81 502 160 | 81 502 162 | Pressure switch | 38 | 81 519 381 | | Miniature solenoid valve | 58 |
| 81 502 230 | 81 502 238 | Amplifier | 33 | 81 519 632 | 81 519 635 | Miniature solenoid valve | 59 |
| 81 502 320 | 81 502 322 | Amplifier | 33 | 81 519 678 | | Miniature solenoid valve | 58 |
| 81 502 435 | 81 502 438 | Relay for leak detector | 31 | 81 519 679 | | Miniature solenoid valve | 58 |
| 81 503 025 | 81 503 028 | YES element | 47 | 81 519 680 | | Miniature solenoid valve | 58 |
| 81 503 540 | 81 503 543 | Timer | 49 | 81 519 732 | | Valve module | 66 |
| 81 503 710 | 81 503 728 | Timer | 50 | 81 519 774 | | Valve module | 66 |
| 81 503 720 | 81 503 729 | Timer | 50 | 81 519 775 | | Valve module | 66 |
| 81 503 725 | 81 503 731 | Timer | 50 | 81 519 776 | | Valve module | 66 |
| 81 504 025 | 81 504 035 | NO element | 22-47 | 81 519 777 | | Valve module | 66 |
| 81 505 110 | 81 505 111 | Vacuum switch | 39 | 81 520 601 | 81 520 602 | Plug-element | 53 |
| 81 505 140 | 81 505 141 | Pressure switch | 38 | 81 521 501 | | OR element | 46 |
| 81 505 150 | 81 505 151 | Pressure switch | 38 | 81 522 501 | 81 522 505 | AND element | 46 |
| 81 505 160 | 81 505 164 | Pressure switch | 38 | 81 523 201 | 81 523 205 | Memory | 48 |
| 81 505 230 | 81 505 231 | Amplifier | 33 | 81 523 601 | 81 523 608 | Memory | 48 |
| 81 505 320 | 81 505 321 | Amplifier | 33 | 81 525 101 | 81 525 106 | Flow restrictor | 52 |
| 81 505 435 | 81 505 437 | Relay for leak detector | 31 | 81 526 001 | 81 526 006 | Flow restrictor | 52 |
| 81 506 025 | 81 506 027 | NO element | 47 | 81 527 001 | | Mini-regulator | 53 |
| 81 506 710 | 81 506 714 | Timer | 50 | 81 529 003 | 81 529 013 | Flow restrictor | 52 |
| 81 506 720 | 81 506 721 | Timer | 50 | 81 529 004 | 81 529 014 | Flow restrictor | 52 |
| 81 506 725 | 81 506 727 | Timer | 50 | | | | |
| 81 506 940 | 81 506 945 | Frequency generator | 51 | | | | |

► List of part numbers

| Industrial part no. | ATEX part no. | Type | Pages | Industrial part no. | ATEX part no. | Type | Pages |
|---------------------|---------------|----------------------------|-------|---------------------|---------------|-----------------------------------|-------|
| 81 529 005 | 81 529 015 | Flow restrictor | 52 | 81 921 911 | | Miniature detector | 27 |
| 81 529 006 | 81 529 016 | Flow restrictor | 52 | 81 921 912 | | Miniature detector | 27 |
| 81 529 007 | 81 529 017 | Flow restrictor | 52 | 81 922 010 | | Compact detector | 28 |
| 81 529 008 | 81 529 018 | Flow restrictor | 52 | 81 922 205 | | Compact detector | 28 |
| 81 529 010 | 81 529 020 | Flow restrictor | 52 | 81 922 210 | | Compact detector | 28 |
| 81 529 025 | 81 529 026 | Flow restrictor | 52 | 81 922 401 | | Compact detector | 28 |
| 81 529 901 | 81 529 907 | Non-return | 53 | 81 923 001 | | Special detector | 30 |
| 81 531 001 | 81 531 008 | Sub-base | 55 | 81 999 501 | | Control pedal | 20 |
| 81 532 001 | 81 532 009 | Sub-base | 55 | 84 000 000 | | | |
| 81 532 102 | 81 532 109 | Sub-base | 54 | 84 150 201 | 84 150 214 | Indicator | 20 |
| 81 532 104 | 81 532 111 | Sub-base | 54 | 84 150 202 | 84 150 215 | Indicator | 20 |
| 81 533 001 | 81 533 001 | Clip domino | 56 | 84 150 203 | 84 150 216 | Indicator | 20 |
| 81 533 501 | 81 533 501 | Hole domino | 56 | 84 150 204 | 84 150 217 | Indicator | 20 |
| 81 535 301 | 81 535 303 | Vacuum generator | 40 | 89 000 000 | | | |
| 81 536 801 | 81 536 804 | Supply base | 56 | 89 538 201 | | Counter | 19 |
| 81 540 001 | 81 540 015 | OR element | 46 | 89 543 101 | | 3/2 NO valve | 14 |
| 81 540 005 | 81 540 017 | OR element | 46 | 89 543 201 | | 3/2 NO valve | 14 |
| 81 541 001 | 81 541 015 | AND element | 47 | 89 543 501 | | 3/2 NF valve | 14 |
| 81 541 005 | 81 541 017 | AND element | 47 | 89 543 701 | | 3/2 NF valve | 14 |
| 81 542 002 | 81 542 004 | Sub-base | 55 | 89 543 005 | | 3/2 NO valve + adaptor | 14 |
| 81 545 001 | 81 545 012 | Vacuum generator | 40 | 89 543 105 | | 3/2 NF valve + adaptor | 14 |
| 81 545 005 | 81 545 013 | Vacuum generator | 40-70 | 89 543 205 | | 3/2 NF valve+3/2 NO valve+adaptor | 14 |
| 81 546 001 | | Miniature solenoid valve | 40-70 | 89 543 305 | | 3/2 NF valve+3/2 NF valve+adaptor | 14 |
| 81 547 001 | | Miniature solenoid valve | 70 | 99 000 000 | | | |
| 81 547 501 | | Miniature solenoid valve | 70 | 99 766 001 | | Counter | 19 |
| 81 548 010 | | Miniature solenoid valve | 71 | 99 766 002 | | Counter | 19 |
| 81 548 011 | | Miniature solenoid valve | 71 | | | | |
| 81 548 012 | | Miniature solenoid valve | 71 | | | | |
| 81 549 010 | | Miniature solenoid valve | 71 | | | | |
| 81 549 011 | | Miniature solenoid valve | 71 | | | | |
| 81 549 012 | | Miniature solenoid valve | 71 | | | | |
| 81 549 510 | | Miniature solenoid valve | 71 | | | | |
| 81 549 511 | | Miniature solenoid valve | 71 | | | | |
| 81 549 512 | | Miniature solenoid valve | 70 | | | | |
| 81 550 001 | 81 550 013 | Register module | 43 | | | | |
| 81 550 201 | 81 550 213 | Register module | 43 | | | | |
| 81 550 401 | 81 550 403 | Register module | 43 | | | | |
| 81 550 601 | 81 550 603 | Register module | 43 | | | | |
| 81 551 001 | 81 551 004 | Sub-base | 45 | | | | |
| 81 551 101 | 81 551 104 | Sub-base | 44 | | | | |
| 81 552 001 | 81 552 005 | Sub-base | 45 | | | | |
| 81 552 101 | 81 552 105 | Sub-base | 44 | | | | |
| 81 552 601 | 81 552 605 | Diversion base | 44 | | | | |
| 81 580 101 | | Pneumatic relay | 17 | | | | |
| 81 580 202 | | Pneumatic relay | 17 | | | | |
| 81 580 503 | | Two-hand control module | 18 | | | | |
| 81 580 504 | | Two-hand control module | 18 | | | | |
| 81 598 940 | | Teaching materials | 73 | | | | |
| 81 598 941 | | Teaching materials | 73 | | | | |
| 81 715 511 | | Push buttons and actuators | 12 | | | | |
| 81 715 512 | | Push buttons and actuators | 12 | | | | |
| 81 716 511 | | Push buttons and actuators | 12 | | | | |
| 81 716 512 | | Push buttons and actuators | 12 | | | | |
| 81 733 511 | | Push buttons and actuators | 12 | | | | |
| 81 735 011 | | Push buttons and actuators | 12 | | | | |
| 81 735 511 | | Push buttons and actuators | 12 | | | | |
| 81 735 512 | | Push buttons and actuators | 12 | | | | |
| 81 737 501 | | Limit switch | 25 | | | | |
| 81 921 501 | | Miniature detector | 26 | | | | |
| 81 921 505 | | Miniature detector | 30 | | | | |
| 81 921 701 | | Miniature detector | 26 | | | | |
| 81 921 702 | | Miniature detector | 26 | | | | |
| 81 921 707 | | Miniature detector | 26 | | | | |
| 81 921 714 | | Miniature detector | 27 | | | | |
| 81 921 717 | | Miniature detector | 27 | | | | |
| 81 921 719 | | Miniature detector | 27 | | | | |
| 81 921 806 | | Miniature detector | 27 | | | | |
| 81 921 901 | | Miniature detector | 27 | | | | |
| 81 921 902 | | Miniature detector | 27 | | | | |



Custom Sensors & Technologies (CST) is a specialist in sensing, control and motion products.

Through its brands, BEI Kimco, BEI Sensors, BEI PSSC, Crouzet, Crydom, Kavlico, Newall and Systron Donner Inertial, CST offers customizable, reliable and efficient components for mission-critical systems in Aerospace & Defence, Transportation, Energy & Infrastructures, Commercial & Industrial OEMs, Medical, Food and Beverage and Building Equipment markets.

Focused on premium value offers and committed to excellence, CST, with more than 4300 employees worldwide and sales of 571M US in 2010, is the dependable and adaptable partner for the most demanding customers.

www.cstsensors.com

Distributed by:

Crouzet Automatismes SAS

2 rue du Docteur Abel - BP 59
26902 Valence CEDEX 9
FRANCE

www.crouzet.com

CRZ BR 54
Réf. 6760011 EN
11/2011

AMERICA

BRAZIL
Custom Sensors & Technologies
Crouzet Latinoamerica
Alameda Rio Negro
1030 - cj 1803 - Alphaville -
Barueri SP - CEP 06454-000
BRASIL
Tel.: +55 (11) 2505 7500
Fax : +55 (11) 2505 7507
E-mail : info@cst-latinoamerica.com
www.crouzet.com.br
www.cst-latinoamerica.com

USA/CANADA
Custom Sensors & Technologies - Crouzet
7230 Hollister Avenue
Goleta, CA, 93117
USA
Tel.: +1 (800) 677 5311
Fax : +1 (800) 677 3865
E-mail : customerservice@us.crouzet.com
www.crouzet.com

MEXICO
Custom Sensors & Technologies - Crouzet
Calzada Zavaleta 2505-C
Santa Cruz Buenavista -
Puebla. 72150 MEXICO
Tel.: +1 (222) 409 7000
Fax : +1 (222) 409 7810
E-mail : mexico@cstsensors.com
www.crouzet.com

OTHER COUNTRIES
Custom Sensors & Technologies
Crouzet Latinoamerica
Alameda Rio Negro
1030 - cj 1803 - Alphaville -
Barueri SP - CEP 06454-000
BRASIL
Tel.: +55 (11) 4195 1834
Fax : +55 (11) 4191 9136
E-mail : info@cst-latinoamerica.com
www.crouzet.com.br
www.cst-latinoamerica.com

EUROPE MIDDLE EAST AFRICA

BELGIUM
Crouzet NV/SA
Dieweg 3 B
B - 1180 Uccle
BELGIUM
Tel.: +32 (0) 2 462 07 30
Fax : +32 (0) 2 461 00 23
E-mail : com-be@crouzet.com
www.crouzet.be

FRANCE
Crouzet Automatismes SAS
2 rue du Docteur Abel - BP 59
26902 Valence CEDEX 9
FRANCE
Tel.: +33 (0) 4 75 44 88 44
Fax : +33 (0) 4 75 55 98 03
E-mail : com-fr@crouzet.com
www.crouzet.fr

Customer service

N°Indigo 0 825 333 350
0.16 € TTC / min

N°AzurFAX 0 810 610 102
Prix Appel Local

Creation-Design: Crouzet Automatismes
Editing-Publishing: Crouzet Automatismes
Photos-Graphics: Daniel Lattard
Printing: Imprimerie des Deux Ponts

ASIA PACIFIC

CHINA & HONG KONG

Custom Sensors & Technologies Asia (Shanghai) Limited - Crouzet
13th floor, Chang Feng International Tower, 89 Yurling Road (East), Putuo District Shanghai 200062 CHINA
Tel. : +86 (21) 6065 6699
Fax : +86 (21) 6065 7749
E-mail : china@cstsensors.com
www.crouzet.cn
www.cstsensors.com

INDIA
CST Sensors India Pvt Ltd
Trident Towers, No 23,
4th Floor,
100 Feet Road, Ashoka Pillar Road,
2nd Block, Jayanagar Bangalore 560 011 INDIA
Tel.: +91 (0) 80 4113 2204/05
Fax : +91 (0) 80 4113 2206
E-mail : crz_bangalore@crouzet.com
www.crouzet.co.in
www.cstsensors.com

TAIWAN & JAPAN

Custom Sensors & Technologies - Crouzet
2F, No. 39, Ji-Hu Road Nei-Hu Dist. - Taipei 114 TAIWAN
Tel. : +886 (0) 287 516 388
Fax : +886 (0) 226 578 725
E-mail : taiwan@cstsensors.com
www.crouzet.com
www.cstsensors.com

KOREA
Custom Sensors & Technologies - Crouzet
2F, Jeil Bldg.
94-96 Youngdeungpo-dong 7-ga Youngdeungpo-gu Seoul 150-037 SOUTH KOREA
Tel. : +82 (0) 2 2629 8312
Fax : +82 (0) 2 2629 8310
E-mail : korea@cstsensors.com
www.crouzet.com
www.cstsensors.com

SOUTH EAST ASIA & PACIFIC

Custom Sensors & Technologies - Crouzet
2F, No. 39, Ji-Hu Road Nei-Hu Dist. - Taipei 114 TAIWAN
Tel. : +886 (0) 287 516 388
Fax : +886 (0) 226 578 725
E-mail : eap@cstsensors.com
www.crouzet.com
www.cstsensors.com

Warning:
The product information contained in this catalogue is given purely as information and does not constitute a representation, warranty or any form of contractual commitment. CROUZET Automatismes and its subsidiaries reserve the right to modify their products without notice. It is imperative that we should be consulted over any particular use or application of our products and it is the responsibility of the buyer to establish, particularly through all the appropriate tests, that the product is suitable for the use or application. Under no circumstances will our warranty apply nor shall we be held responsible for any application (such as any modification, addition, deletion, use in conjunction with other electrical or electronic components, circuits or assemblies, or any other unsuitable material or substance) which has not been expressly agreed by us prior to the sale of our products.

